

## Canon EOS 1D X Mark II



Rating: 4.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 3,184.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Canon](#)

### Description

- 20.2MP Full-Frame CMOS Sensor
- Dual DIGIC 6+ Image Processors
- 14 fps Shooting, 16 fps in Live View
- DCI 4K Video at 60 fps, 8.8MP Still Grab
- 61-Point High Density Reticular AF II
- 3.2 inch (1.62m) Touchscreen LCD Monitor
- Dual Pixel CMOS AF and Movie Servo AF
- ISO 100-51200 (Expanded to 409600)
- Built-In GPS
- CFast & CF Card Slots

### Product Details

Immense power. Phenomenal speed. A remarkable combination of innovation and refinement. The EOS-1D X Mark II camera is nothing but legendary every step of the way. Building on a heritage of sophisticated innovation, the EOS-1D X Mark II is blazingly fast. Up to 14 fps (up to

16 fps in Live View mode) can be captured at a burst rate of up to 170 RAWs with a CFast™ card, and an improved 61-point AF system helps deliver clean, sharp images quickly, even in dim light. This remarkable speed means faster recording too: 4K video can be recorded at up to 60 fps with smooth AF and strikingly clear detail. Combined with superb low-light performance thanks to its powerful sensor and expandable ISO range, the EOS-1D X Mark II performs brilliantly, swiftly and stunningly no matter when or where the photographer is shooting. From the stadium, safari or studio to virtually everywhere in between, the EOS-1D X Mark II maintains and enhances all the hallmarks of what Canon has to offer, marking a new page in the legacy of the EOS series of cameras.

**What's in the box :**

- 1. Canon EOS-1D X Mark II Camera Body
- 2. Battery Pack LP-E19
- 3. Battery Charger LC-E19
- 4. Wide Strap
- 5. Eyecup Eg
- 6. Cable Protector
- 7. Interface Cable IFC-150U II
- 8. EOS Digital Solution Disk

System Cameras (1)	
General	
Camera Type:	Digital, AF/AE single-lens reflex camera
Image Sensor	
Sensor Type:	CMOS
Sensor Size:	35.9 x 23.9 mm
Effective Megapixels:	20.2
Viewfinder	
Viewfinder Type:	Pentaprism
Coverage:	100 %
Exposure & Shutter Control	
Min. ISO Sensitivity:	100
Max. ISO Sensitivity:	51200
Min. Shutter Speed:	Bulb sec
Max. Shutter Speed:	1/8000 sec
Continuous Burst Speed:	14 ( 16fps in Live View mode) fps
Maximum Shots / Burst:	unlimited number of JPEGs or 170 RAW images
Video Recording	
File Format:	MOV
Video Resolution:	4096 x 2160
HD Recording:	Yes
Display	
LCD Size:	3.2 inch
LCD Resolution:	1620 k pixels
Live View:	Yes

Storage	
Memory	CompactFlash
Card	Type I and CFast
Type:	2.0
Internal	-
Memory:	
Power Supply	
Battery	LP-E19
Model:	
Battery	-
Grip:	
Dimensions	
Size:	158 X 167.6 X
	82.6 mm
Weight:	1340 g
Camera Features	
Image Sta No	
bilization	
Sensor	Yes
Cleaning:	
Tilt / Flip	No
Screen :	
Full Auto:	No
Face Dect	Yes
ection :	
HDMI Co	Yes
nnection:	
External	Remote control
Remote	with N3 type
Control:	contact