

Canon EOS 5D Mark III With EF 24-105mm Lens Kit



Rating: 5.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,499.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Canon](#)

Description

- 22.3 Megapixel full-frame CMOS sensor
- All new 61-Point High Density Reticular AF
- Up to 6fps High-Speed continuous shooting
- Native ISO 100-25,600 sensitivity
- 3.2 inch (1040k)TFT LCD Monitor
- Full HD video with manual control
- 14 bit DIGIC 5+ Image processor
- Enhanced Weather sealing
- HDR mode with presets

What's in the Box :

1. Canon EOS 5D Mark III Body
2. Canon EF 24-105mm f/4.0 L IS USM Lens
3. Battery Pack LP-E6
4. Battery Charger LC-E6

5. Eyecup
6. Wide Neck Strap EW-EOS 5D Mark III
7. Stereo AV Cable AVC-DC400ST
8. USB Interface Cable IFC-200U
9. EOS Digital Solution Disc
10. Software Instruction Manual

System Cameras (1)	
General	
Camera	Digital, AF/AE
Type:	single-lens reflex, camera
Image Sensor	
Sensor	Digital, AF/AE
Type:	single-lens reflex, camera
Sensor Size:	36 x 24 mm
Effective Megapixels:	22.3
Viewfinder	
Viewfinder Type:	Eye-level pentaprism
Coverage:	100 %
Exposure & Shutter Control	
Min. ISO Sensitivity	ISO 50
:	
Max. ISO Sensitivity	ISO 102400
:	
Min. Shutter Speed:	30 sec
Max. Shutter Speed:	1/8000 sec
Continuous Burst Speed:	6 fps
Maximum Shots / Burst:	65 shots
Video Recording	
File Format:	MPEG-4 AVC / H.264
Video Reso- lution:	1920 x 1080
HD Recording	Yes
Display	
LCD Size:	3.2 inch
LCD Reso- lution:	1040 k pixels
Live View:	Yes
Storage	
Memory Card Type:	CF Cards (Type I); Compatible with UDMA CF cards; SD, SDHC, and SDXC Memory Cards

Internal -
Memory:
Power Supply
Battery LP-E6
Model:
Battery BG-E11
Grip:
Dimensions
Size: 152 X 116.4 X
76.4 mm
Weight: 860 g
Camera Features
Image Stabilization
Sensor Yes
Cleaning:
Tilt / Flip No
Screen :
Full Auto: No
Face Detection :
HDMI Connection: Yes
External Remote control
Remote with N3 type
Control: contact,
Wireless
Controller LC-5,
Remote
Controller RC-6