Canon EOS 70D Digital Camera DSLR Body



Rating: 5.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 444.00

Discount:

In Stock!
Ready to Order

Ask a question about this product

Manufacturer: Canon

Description

- 20.2 Megapixel APS-C CMOS sensor
- DIGIC 5+ Image Processor
- Dual Pixel CMOS AF with Live View
- 3.0 inch (1040k) Vari-Angle Clear View II Touch Screen
- ISO 100-12800, Expandable to 25600
- 7.0 fps Continuous Shooting
- 19-Point All Cross-Type AF System
- Wi-Fi file transfer and remote control
- Full HD 1080p Movie Mode with Movie Servo AF

What’s in the box

1. Canon EOS 70D Digital DSLR Body
2. Eyecup Eb
3. Body cap
4. Wide Strap
5. Battery Pack LP-E6

6. Battery Charger
7. USB Interface Cable
8. EOS Digital Solution Disc
9. Software Instruction Manual CD

System Cameras (1)	
General	
Camera Type:	Digital SLR
Image Sensor	
Sensor Type:	CMOS
Sensor Size:	22.5mm x 15.0mm mm
Effective Megapixels:	20.20 MP
Viewfinder	
Viewfinder Type:	Pentaprism
Coverage:	98 %
Exposure & Shutter Control	
Min. ISO Sensitivity:	100
Max. ISO Sensitivity:	12800 Expandable to 25600
Min. Shutter Speed:	30 sec
Max. Shutter Speed:	1/8000 sec
Continuous Burst Speed:	7.0 fps
Maximum Shots / Burst:	Max. Approx. 7fps. (speed maintained for up to 65 images (JPEG)[13](with UHS-I card), 16 images (RAW))[23]
Video Recording	
File Format:	MOV (Video: H.264 Intra frame / inter frame, Sound: Linear PCM, recording level can be manually adjusted by user)
Video Resolution:	1920 x 1080 (29.97, 25, 23.976 fps) intra or inter frame 1280 x 720 (59.94, 50 fps) intra or inter frame 640 x 480 (29.97, 25 fp

HD Recording	Yes
Display	
LCD Size:	3.0 inch
LCD Resolution:	1040 k pixels
Live View:	Yes
Storage	
Memory Card Type:	SD, SDHC or SDXC (UHS-I)card
Internal Memory:	-
Power Supply	
Battery Model:	LP-E6
Battery Grip:	BG-E14
Dimensions	
Size:	139.0 X 104.3 X 78.5 mm
Weight:	755 g
Camera Features	
Image Stabilization	Yes
Sensor Cleaning:	Yes
Tilt / Flip Screen :	Yes
Full Auto:	Yes
Face Dection :	No
HDMI Connection:	Yes
External Remote Control:	Remote Switch RS-60E3, Remote Controller RC-6