

## Canon imagePROGRAF iPF8400SE 44in Printer



Rating: 3.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,249.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Canon](#)

### Description

**Item:** 8572B002

**UPC:** 013803230826

Printing Method	FINE (Full-photolithography Inkjet Nozzle Engineering)
Printing Technology	2400 x 1200 dpi
Maximum Resolution	4 picoliter
Ink Droplet Size	LUCIA EX pigment-based ink
Ink Type	Red, cyan, magenta, yellow, black, and matte black
Ink Cartridge Configuration	PFI-306 series
Compatible Ink Cartridges	PFI-706 series
Number of Nozzles	Total: 15,360
	Per Color: 2,560
Nozzle Pitch	1,200 dpi
	Non-firing nozzle detection and compensation

# Printers : Canon imagePROGRAF iPF8400SE 44in Printer

---

Print Speed	Fast Draft Mode (1200 x 1200 dpi): 705 ft <sup>2</sup> /hr (65 m <sup>2</sup> /hr)
Paper Handling	Front-loading roll feed Front-loading manual feed
Paper Types	Cut sheet and roll
Paper Size	<b>Cut Sheet Width</b> 8 to 44" (20.3 to 111.8 cm) <b>Roll Feed Width</b> 10 to 44" (25.4 to 111.8 cm) <b>Manual Feed Length</b> 8 to 63" (20.3 cm to 1.6 m) <b>Roll Feed Length</b> 8" to 59' (20.3 cm to 18 m)
Borderless Photo Sizes	Roll Widths: 10" (25.4 cm), 14" (35.6 cm), 17" (43.2 cm), 24" (61.0 cm), 36" (91.4 cm), 42" (106.7 cm), 44" (111.8 cm), B2 20.3" (51.5 cm), A1 23.4" (59.4 cm), A0 33.1" (84.1 cm), B0 40.6" (103.0 cm)
Margins	Front Manual Feed, Leading Edge: 0.2" (5 mm) Front Manual Feed, Trailing Edge: 0.9" (23 mm) Front Manual Feed, Top: 0.79" (20 mm) Roll Feed, All Sides: 0.2" (5 mm) or 0" for borderless
Media Thickness	2.8-31.4 mil (0.07-0.80 mm)
Maximum Media Roll Diameter	5.9" (15.0 cm) Core Sizes: 2 or 3" (5.1 or 7.6 cm)
Connectivity	
Interfaces	USB 2.0 10/100Base-T/TX Ethernet
OS Compatibility	Windows XP (32/64-bit), Server 2003 (32/64-bit), Server 2008 (32/64-bit), Vista (32/64-bit), 7 (32/64-bit), 8 (32/64-bit) Macintosh OS X 10.5.8-10.7.x
Memory	384
Printer Language	GARO
Physical	
Power Requirements	100-240 VAC, 50-60 Hz
Power Consumption	Maximum: 190 W or less Standby: 5 W or less Power Off: 0.5 W or less
Certifications	UL, FCC Class B, ENERGY STAR
Acoustic Noise	Operating: 50 dB (A) or less Standby: 35 dB (A) or less Acoustic Power: 6.8 Bels or less
Operating Conditions	Temperature: 59 to 86°F (15 to 30°C) Humidity: 10-80%, non-condensing
Dimensions (H x W x D)	45.0 x 74.5 x 28.9" (114.3 x 189.2 x 73.4 cm)
Weight	258 lb (117 kg) with stand