

Canon imagePROGRAF iPF9400S 60in Printer



Rating: 3.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 3,349.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Canon](#)

Description

Item: 6562B002AA

UPC: 013803150766

Printing Method	Color inkjet printer with non-firing nozzle detection and compensation
Printing Technology	2400 x 1200 dpi
Maximum Resolution	Cyan, Photo Cyan, Magenta, Photo Magenta, Yellow, Black, Matte
Print Color	Black, Gray
Ink Droplet Size	4.0 pl
Ink Type	Pigment-based (LUCIA EX Ink)
Ink Tank Configuration	8 individual ink tanks
Compatible Ink Tanks	PFI-306 Cyan Ink Tank PFI-306 Photo Cyan Ink Tank PFI-306 Magenta Ink Tank PFI-306 Photo Magenta Ink Tank

Printers : Canon imagePROGRAF iPF9400S 60in Printer

	PFI-306 Yellow Ink Tank PFI-306 Black Ink Tank PFI-306 Matte Black Ink Tank PFI-306 Gray Ink Tank PFI-706 Cyan Ink Tank PFI-706 Photo Cyan Ink Tank PFI-706 Magenta Ink Tank PFI-706 Photo Magenta Ink Tank PFI-706 Yellow Ink Tank PFI-706 Black Ink Tank PFI-706 Matte Black Ink Tank PFI-706 Gray Ink Tank
Ink Tank Capacity	11.2 fl oz (330.0 ml) 23.7 fl oz (700.0 ml)
Number of Nozzles	Total: 20,480 Per Color: 2,560
Nozzle Pitch	1200 dpi
Paper Handling	Front Loading Manual Feed, 1 sheet, front output
Paper-Feed Method	Plain, Coated, Photo, Glossy, Proofing, CAD
Paper Types	JIS B2: 20.3" (51.5 cm), JIS B0: 40.6" (103.0 cm), ISO A1: 23.4" (59.4 cm), ISO A0: 33.1" (84.1 cm), 10.0" (25.4 cm), 14.0" (35.56 cm), 17.0" (43.18 cm), 24.0" (60.96 cm), 36.0" (91.44 cm), 42.0" (106.68 cm)
Borderless Printing Width	Ledger, Super B, Letter, Legal
Paper Sizes	ISO: A0, A1, A2, A2+, A3, A3+, A4, B0, B1, B2, B3, B4 JIS: B0, B1, B2, B3, B4 ANSI: C, D, E, F ARCH: A, B, C, D, E, E1, E2, E3 DIN: C0, C1, C2, C3, C4 20.0 x 24.0" (50.8 x 60.96 cm), 18.0 x 22.0" (45.72 x 55.88 cm), 14.0 x 17.0" (35.56 x 43.18 cm), 12.0 x 16.0" (30.48 x 40.64 cm), 10.0 x 12.0" (25.4 x 30.48 cm), 10.0 x 15.0" (25.4 x 38.1 cm), 8.0 x 10.0" (20.32 x 25.4 cm) US Photo 16.0 x 20.0" (40.64 x 50.8 cm) Poster: 20.0 x 30.0" (50.8 x 76.2 cm), 30.0 x 40.0" (76.2 x 101.6 cm), 42.0 x 60.0" (106.68 x 152.4 cm), 44.0 x 62.0" (111.76 x 157.48 cm), 50.0 x 70.0" (127.0 x 177.8 cm), 54.0 x 76.0" (137.16 x 193.04 cm), 60.0 x 84.0" (152.4 x 213.36 cm), 13.0 x 22.0" (32.9 x 55.88 cm), 11.81 x 35.43" (30.0 x 90.0 cm) Sheet: 60.0 x 63.0" (1.5 x 1.6 m) Roll: 60.0" x 59.0' (1.5 x 18.0 m) 59.0' (18.0 m) Front-Loading Manual Feed: 2.8 to 31.4 mil (0.07 to 0.8 mm) Roll: 2.8 to 31.4 mil (0.07 to 0.8 mm) 5.9" (150.0 mm) 2.0, 3.0" (5.08, 7.62 cm)
Maximum Printable Area	USB 2.0 High-Speed 10/100/1000 Base-T/TX Ethernet
Maximum Roll Print Length	Windows: XP, Vista (32, 64-bit), Windows 7 (32, 64-bit)
Media Thickness	Mac: OS X
Maximum Media Roll Diameter	Canon Printer Driver, Printer Driver Extra Kit (Free Layout, Color imageRUNNER Enlargement Copy, Advanced Preview), Print Plug-in for Adobe Photoshop, Print Plug-in for Microsoft Word, Excel, and PowerPoint (PC only), Accounting Manager
Core Sizes	640 MB
Connectivity	250 GB
Interfaces	GARO
OS Compatibility	100 to 240 V AC, 50 to 60 Hz
Included Software	Maximum: 190 W Standby: ? 6.0 W Power Off: ? 0.5 W
Input Buffer	DoD5022.22-M, International Energy Star Program (worldwide), Law on Promoting Green Purchasing (Japan), GPN, RoHS directive, IT Eco Declaration (Europe), WEEE, US presidential directives, J-MOSS (Green Mark), Chinese RoHS, ErP Lot6 (Europe)
Hard Drive Capacity	Operating Sound Pressure: 52 dB (A)
Printer Language	Standby Sound Pressure: ? 35 dB (A)
Physical	
Power Requirements	
Power Consumption	
Certifications	
Acoustic Noise	

Temperature / Humidity

Dimensions (WxDxH)

Weight

Packaging Info

Package Weight

Box Dimensions (LxWxH)

Operating Sound Power Level: ~ 6.8 B
Operating Temperature: 59 to 86°F (15 to 30°C)
Operating Humidity: 10 to 80%
90.5 x 30.2 x 45.0" (229.9 x 76.7 x 114.3 cm)
~ 355.0 lb (161.0 kg) with stand

365.0 lb
97.5 x 48.0 x 39.5"