Canon imagePROGRAF PRO-2000 24in Printer



Rating: 5.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,348.00

Discount:

In Stock!
Ready to Order

Ask a question about this product

Manufacturer: Canon

Description

Item: 1124C002AA

Printing Method	
Printing Technology	FINE: Full-Photolithography Inkjet Nozzle Engineering
Maximum Resolution	2400 x 1200 dpi
Ink Type	Pigment-based
Ink Cartridge Configuration	12 individual cartridges
Number of Nozzles	1,536 nozzles x 12 channels Total: 18,432
Minimum Ink Droplet Size	4 pL
Media Handling	
Paper Handling	Front-loading roll feed (one roll, front output) Front-loading manual feed (front output)

Media Width	8-24" / 20.3-61 cm
Borderless Printing Width	10" / 25.4 cm, 14" / 35.6 cm, 17" / 43.2 cm, 24" / 61 cm, B4 9.8" / 25 cm, A3 11.7" / 29.7 cm, A2 16.5" / 42 cm, B2 19.7" / 50 cm, A1 23.4" / 59.4 cm
Minimum Length	8" / 20.3 cm
Maximum Length	Roll Paper: 59' / 18 m Cut Sheet: 63" / 160 cm
Media Thickness	2.8-31.5 mil / 0.07-0.8 mm
Margins	**Roll Paper** Top: 0.12" / 3 mm Bottom: 0.12" / 3 mm Side: 0.12" / 3 mm **Borderless** Top: 0" / 0 mm Bottom: 0" / 0 mm Side: 0" / 0 mm **Cut Sheet** Top: 0.12" / 3 mm Bottom: 0.79" / 20 mm Side: 0.12" / 3 mm
Maximum Roll Diameter	6.7" / 17 cm
Core Sizes	2 or 3" / 5.1 or 7.6 cm
Connectivity	
Interfaces	USB 2.0 Ethernet (10/100/1000Base-T/TX) Wi-Fi (IEEE 802.11b/g/n)
Direct Printing	USB Wi-Fi
OS Compatibility	Windows 10, 8.1, 8, 7, Vista (32/64-bit) Mac OS X 10.7.5-10.11.x
Memory	3 GB
Hard Disk Capacity	320 GB
Print Languages	Swift Graphic Raster (SGRaster)
Physical	
Control Panel	3.5" / 8.9 cm color touchscreen LCD
Power Requirements	100-240 VAC, 50-60 Hz
Power Consumption	Maximum: 88 W Standby: 1.8 W Off: 0.5 W
Certifications	ENERGY STAR RoHS Directive
Acoustic Noise	48 dB(A)
Operating Conditions	Temperature: 59 to 86°F / 15 to 30°C Humidity: 10 to 80%
Dimensions	46 x 43.7 x 38.7" / 116.8 x 111 x 98.3 cm with basket open
Weight	223 lb / 101.2 kg