

## DJI Phantom 3 Advanced with 2.7K Camera Bundle with Wheeled Hard Case and SD Card



Rating: 5.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 511.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Dji](#)

Description

### Product Highlights

- Gimbal Stabilized 2.7K Camera
- Camera Takes 12MP Still Photos

- App for Monitoring / Camera Operation
- Gimbal Control Dials on Transmitter
- GPS for Enhanced Stability and Failsafes
- Auto-Takeoff / Auto Return Home
- Vision Sensor for Indoor Flight
- Up to 23 Minutes Flying Time
- Includes 1 Intelligent Flight Battery
- Mobile Device Holder Included

**DJI Phantom 3 Advanced Quadcopter with 2.7K Camera and 3-Axis Gimbal**

## Performance

Maximum Speed	Ascent: 16.4' / 5 m/s Descent: 9.8' / 3 m
Hover Accuracy	Vertical: $\pm 3.9''$ / 10 cm Horizontal: $\pm 3.3'$ / 1 m
Maximum Altitude	Above Sea Level: 19,685' / 6000 m
Flight Time	23 minutes (depending on conditions)
Flight Control System	
GPS Mode	GPS / GLONASS
Vision Positioning	<b>Frequency:</b> 50 Hz <b>Velocity Range:</b> Below 26.2 fps / 8 m/s (6.6' / 2 m above the ground) <b>Altitude Range:</b> 11.8" to 118.1" / 30 cm to 300 cm <b>Operating Range:</b> 11.8" to 118.1" / 30 cm to 300 cm

**Operating Environment:** Surface with clear pattern and adequate lighting (> 15 lux)

## Transmitter

Frequency	2.400 to 2.483 GHz
Communication Distance	Up to 3.1 miles / 5 km (outdoors and unobstructed)
Receiver Sensitivity	1%PER: 101 dBm $\pm 2$ dBm
Transmitter Power	EIRP: 20 dBm
Working Current	1.2 A at 7.4 V
Connectivity	1 x USB type A female for mobile device interface 1 x Micro-USB female for firmware updates / assistant software 1 x Charge port
Lightbridge Support	Yes; compatible iOS or Android mobile device with USB required
Mobile Device Holder	Compatibility: Tablet or smartphone
Operating Temperature	32 to 104°F / 0 to 40°C

## Camera

## Sensor

Make: Sony EXMOR  
Size: 1/2.3"  
Resolution: 12.76 MP (12.4 MP effective)  
Aperture: f/2.8  
FOV: 94°  
Focal Length: 20 mm (35 mm equivalent)  
Elements: 9  
Focus: 0 to ?

## Photo Resolution

## ISO Range

Up to 12 MP (4000 x 3000)  
Video: 100 to 3200  
Photo: 100 to 1600

## Video Resolutions

**2.7K (2704 x 1520):** 30p, 25p, 24p  
**1080p (1920 x 1080):** 24p, 25p, 30p, 48p, 50p, 60p  
**720p (1280 x 720):** 24p, 25p, 30p, 48p, 50p, 60p

## Photo Modes

Single Shot  
Burst Shooting: 3/5/7 shots  
Auto Exposure Bracketing (AEB): 3/5  
Bracketed Frames at 0.7 EV Bias

## File Formats

Time-lapse  
Video: MPEG-4 AVC/H.264 in MOV wrapper (up to 60 Mbps)  
Photo: JPEG, DNG RAW

## Recording Media

Type: microSD/SDXC card up to 64 GB  
Format: FAT32 / exFAT

## Operating Temperature

**Note:** Class 10, UHS-1 or faster card required  
32 to 104°F / 0 to 40°C

## Gimbal

## Number of Axes

3-axis (pitch, roll, yaw)

## Control Range

-90° to +30°

## Motor

---

Type	Brushless
Recommended Takeoff Weight	10.6 oz / 300 g per axis
Maximum Tension	1.8 lb / 800 g per axis
Stator Size	0.9 x 0.5" / 23 x 12 mm
Motor Velocity Constant	KV: 960 rpm/V
Working Temperature	23 to 104°F / -5 to 40°C
Weight	1.9 oz / 55 g
Flight Battery	
Chemistry	Lithium-polymer
Capacity	4480 mAh
	68 Wh
Configuration	4S
Voltage	15.2 VDC
Weight	12.9 oz / 365 g
Maximum Charging Power	100 W
Operating Temperature	32 to 104°F / 0 to 40°C
Charger	Voltage: 17.4 VDC
	57 W
Mobile App	
Name	DJI Pilot
System	<b>OS:</b> iOS 8.0 or
Requirements	later; Android 4.1.2 or later
	<b>Recommended Devices:</b>
	<b>Apple (iOS):</b>
	iPhone 5s, iPhone 6, iPhone 6 Plus, iPad Air (Wi-Fi and cellular versions), iPad mini 2 (Wi-Fi and cellular versions), iPad Air 2 (Wi-Fi and cellular versions), iPad mini 3 (Wi-Fi and cellular versions)
	<b>(Note:</b> Optimized for iPhone 5s, iPhone 6, and iPhone 6 Plus)
	<b>Samsung</b>
	<b>(Android):</b> Galaxy Tab SM-T705C, Galaxy S6, Galaxy Galaxy S5, Galaxy Note4, Note3
	<b>Other (Android):</b>
	Google Nexus 9, Google Nexus 7 II, Ascend Mate7, Huawei P8 Max, Nubia Z7 mini, Sony Xperia Z3, MI 3, MI PAD, Smartisan T1
	<b>Note:</b> Additional devices may be compatible but have not yet been tested
General	
Operating Temperature	32 to 104°F / 0 to 40°C
Dimensions	Diagonal (Including Propellers): 23.2" / 590 mm

---

Weight	Including Battery and Propellers: 2.8 lb / 1.3 kg
Packaging Info	
Box Dimensions (LxWxH)	15.6 x 14.3 x 8.5"