

## DJI Phantom 3 Professional with 4K Camera and Battery Bundle



Rating: 1.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 679.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Dji](#)

### Description

#### Product Highlights

- Gimbal Stabilized 4K Camera
- Camera Takes 12MP Still Photos
- App for Monitoring / Camera Operation
- Gimbal Control Dials on Transmitter
- GPS for Enhanced Stability and Failsafes
- Auto-Takeoff / Auto Return Home
- Vision Sensor for Indoor Flight
- Up to 23 Minutes Flying Time

## Drone : DJI Phantom 3 Professional with 4K Camera and Battery Bundle

---

- Includes 2 Intelligent Flight Batteries
- Mobile Device Holder Included

### DJI Phantom 3 Professional Quadcopter with 4K Camera and 3-Axis Gimbal

Performance	
Maximum Speed	Ascent: 16.4' / 5 m/s Descent: 9.8' / 3 m
Hover Accuracy	Vertical: $\pm 3.9''$ / 10 cm Horizontal: $\pm 3.3'$ / 1 m
Maximum Altitude	Above Sea Level: 19,685' / 6000 m
Flight Time	23 minutes (depending on conditions)
Flight Control System	
GPS Mode	GPS / GLONASS
Vision Positioning	<b>Frequency:</b> 50 Hz <b>Velocity Range:</b> Below 26.2 fps / 8 m/s (6.6' / 2 m above the ground) <b>Altitude Range:</b> 11.8" to 118.1" / 30 cm to 300 cm <b>Operating Range:</b> 11.8" to 118.1" / 30 cm to 300 cm
	<b>Operating Environment:</b> Surface with clear pattern and adequate lighting (> 15 lux)
Transmitter	
Frequency	2.400 to 2.483 GHz
Communication Distance	Up to 3.1 miles / 5 km (outdoors and unobstructed)
Receiver Sensitivity	1%PER: 101 dBm $\pm 2$ dBm
Transmitter Power	EIRP: 20 dBm
Working Current	1.2 A at 7.4 V
Connectivity	1 x USB type A female for mobile device interface 1 x Micro-USB female for firmware updates / assistant software 1 x Charge port
Lightbridge Support	Yes; compatible iOS or Android mobile device with USB required
Mobile Device Holder	Compatibility: Tablet or smartphone
Operating Temperature	32 to 104°F / 0 to 40°C
Camera	
Sensor	Make: Sony EXMOR Size: 1/2.3"
	Resolution: 12.76 MP (12.4 MP effective) Aperture: f/2.8 FOV: 94° Focal Length: 20 mm (35 mm equivalent) Elements: 9 Focus: 0 to ?
Lens	Up to 12 MP (4000 x 3000) Video: 100 to 3200 Photo: 100 to 1600
Photo Resolution	<b>DCI 4K (4096 x 2160):</b> 24p, 25p <b>UHD 4K (3840 x 2160):</b> 24p, 25p, 30p <b>1080p (1920 x 1080):</b> 24p, 25p, 30p, 48p, 50p, 60p <b>720p (1280 x 720):</b> 24p, 25p, 30p, 48p, 50p, 60p
ISO Range	Single Shot Burst Shooting: 3/5/7 shots Auto Exposure Bracketing (AEB): 3/5 Bracketed Frames at 0.7 EV Bias Time-lapse
Video Resolutions	Video: MPEG-4 AVC/H.264 in MOV wrapper (up to 60 Mbps) Photo: JPEG, DNG RAW Type: microSD/SDXC card up to 64 GB Format: FAT32 / exFAT
Photo Modes	<b>Note:</b> Class 10, UHS-1 or faster card required 32 to 104°F / 0 to 40°C
File Formats	
Recording Media	
Operating Temperature	
Gimbal	
Number of Axes	3-axis (pitch, roll, yaw)
Control Range	-90° to +30°
Motor	
Type	Brushless
Recommended Takeoff Weight	10.6 oz / 300 g per axis
Maximum Tension	1.8 lb / 800 g per axis
Stator Size	0.9 x 0.5" / 23 x 12 mm
Motor Velocity Constant	KV: 960 rpm/V

Working Temperature	23 to 104°F / -5 to 40°C
Weight	1.9 oz / 55 g
Flight Battery	
Chemistry	Lithium-polymer
Capacity	4480 mAh
	68 Wh
Configuration	4S
Voltage	15.2 VDC
Weight	12.9 oz / 365 g
Maximum Charging Power	100 W
Operating Temperature	32 to 104°F / 0 to 40°C
Charger	Voltage: 17.4 VDC
	100 W

## Mobile App

Name	DJI Pilot
System	<b>OS:</b> iOS 8.0 or
Requirements	later; Android 4.1.2
	or later

## Recommended Devices:

### Apple (iOS):

iPhone 5s, iPhone 6, iPhone 6 Plus, iPad Air (Wi-Fi and cellular versions), iPad mini 2 (Wi-Fi and cellular versions), iPad Air 2 (Wi-Fi and cellular versions), iPad mini 3 (Wi-Fi and cellular versions)

**(Note:** Optimized for iPhone 5s, iPhone 6, and iPhone 6 Plus)

### Samsung

**(Android):** Galaxy Tab SM-T705C, Galaxy S6, Galaxy Galaxy S5, Galaxy Note4, Note3

### Other (Android):

Google Nexus 9, Google Nexus 7 II, Ascend Mate7, Huawei P8 Max, Nubia Z7 mini, Sony Xperia Z3, MI 3, MI PAD, Smartisan T1

**Note:** Additional devices may be compatible but have not yet been tested

## General

Operating Temperature	32 to 104°F / 0 to 40°C
Dimensions	Diagonal (Including Propellers): 23.2" / 590 mm
Weight	Including Battery and Propellers: 2.8 lb / 1.3 kg
Packaging Info	
Box Dimensions (LxWxH)	15.4 x 14.3 x 8.3"

