

## EPSON SureColor T3270 24in Printer



Rating: 2.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,147.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Epson](#)

Description

**Item:** SCT3270SR

Printing Method

Printing Technology

Maximum Resolution

Print Speed

Minimum Ink Droplet Size

Ink Type

Ink Cartridge Configuration

Compatible Ink Cartridges

PrecisionCore TFP Printhead and Micro-Electro-Mechanical Systems with Variable Size Ink Droplet Technology

2880 x 1440 dpi

Speed: 660 ft<sup>2</sup> (61.3 m<sup>2</sup>) per hour

Production: 275 ft<sup>2</sup> per hour

High Quality: 105 ft<sup>2</sup> per hour

28 seconds for D-size 22 x 34" (55.9 x 86.4 cm) plot

3.5 pl

UltraChrome XD pigment-based ink

Cyan, Yellow, Magenta, Matte Black, Photo Black

T692100 Photo Black Ink Cartridge (110 ml)

	T692200 Cyan Ink Cartridge (110 ml) T692300 Magenta Black Ink Cartridge (110 ml) T692400 Yellow Black Ink Cartridge (110 ml) T692500 Matte Black Ink Cartridge (110 ml) T693100 Photo Black Ink Cartridge (350 ml) T693200 Cyan Ink Cartridge (350 ml) T693300 Magenta Black Ink Cartridge (350 ml) T693400 Yellow Black Ink Cartridge (350 ml) T693500 Matte Black Ink Cartridge (350 ml) T694100 Photo Black Ink Cartridge (700 ml) T694200 Cyan Ink Cartridge (700 ml) T694300 Magenta Black Ink Cartridge (700 ml) T694400 Yellow Black Ink Cartridge (700 ml) T694500 Matte Black Ink Cartridge (700 ml)
Number of Nozzles	Per Color: 720 Total: 3600
Line Accuracy	±0.1%
Minimum Line Width	0.7 mil (0.018 mm)
Media Handling	
Paper Types	Roll
Paper Sizes	Cut-sheet Roll: 10.0-24.0" (25.4-61.0 cm) wide on 2" (5.1 cm) or 3" (7.6 cm) core Cut-sheet: 8.3-24.0" (21.0-61.0 cm) wide
Borderless Printing	10" (25.4 cm), 11.8" (30.0 cm), 13" (33.0 cm), 16" (40.6 cm), 17" (43.2 cm), 20.3" (51.6 cm), 23" (58.4 cm), 24" (61.0 cm)
Media Thickness	3.1-59.1 mil (0.08-1.50 mm)
Connectivity	
Interfaces	USB 2.0 10/100/1000 Base-T Ethernet
Print Languages	Epson Precision XD and Native HPGL, HPGL/2, HP-RTL
Network Protocol Support	TCP/IP IPv4 and IPv6, Apple Bonjour, FTP, WSD, RAW IP, LPD, IPSec, SSL/TLS, and IEEE802.1X authentication
Compatible Operating Systems	Windows 8, 7, Server 2012, Server 2008 Mac OS X 10.9, 10.8, 10.7
Physical	
Control Panel	Full color LCD with buttons
Power Requirements	100-240 VAC, 50-60 Hz
Power Consumption	Operating: 52 W Sleep: Off: <0.5 W
Certifications	UL (MET), FCC (Class A), CSA, TCSA, CE, EMC, and ENERGY STAR 2.0
Operating Conditions	Temperature: 50 to 95°F (10 to 35°C) Humidity: 20 to 80%, non-condensing
Dimensions (WxDxH)	42 x 30 x 44" (107 x 76 x 112 cm) with stand
Weight	148 lb (67 kg) with stand
Packaging Info	
Package Weight	148.0 lb
Box Dimensions (LxWxH)	49.0 x 44.5 x 31.0"