

HP Color LaserJet Enterprise M750dn Laser Printer



Rating: 4.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,424.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

Item: HEWD3L09A

Part: D3L09A#BGJ

UPC: 887758123294

Performance

Printing Technology

Maximum Resolution

Print Speed

First Print Out Speed

Print Color

Laser; HP ImageREt 3600

600 x 600 dpi

30 ppm

10 seconds

CMYK

Printers : HP Color LaserJet Enterprise M750dn Laser Printer

| | |
|--------------------------|--|
| Duplex Printing | Automatic |
| Printer Duty Cycle | Up to 120,000 pages |
| Print Features | Recommended Monthly Volume: 2,500 to 13,000 pages HP ePrint, Open Extensibility Platform, FutureSmart Firmware, HP Easy Color, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs |
| Media Handling | Multipurpose tray |
| Paper Handling | Input tray 2 Input tray 3 Output bin |
| Paper Types | Paper (extra heavy, glossy, heavy, heavy glossy, high gloss images, intermediate, light, plain, recycle, tough), envelopes, labels, cardstock, transparencies |
| Paper Sizes | Multipurpose Tray: 3 x 5" / 7.6 x 12.7 cm, 4 x 6" / 10.2 x 15.2 cm, statement, 5 x 7" / 12.7 x 17.8 cm, 5 x 8" / 12.7 x 20.3 cm, letter, letter-R, legal, executive, 11 x 17" / 27.9 x 43.2 cm, 8.5 x 13" / 21.6 x 33 cm, 12 x 18" / 30.5 x 45.7 cm, #9/10/Monarch envelopes Trays 2 & 3: Letter, letter-R, legal, executive, 8.5 x 13" / 21.6 x 33 cm, 11 x 17" / 27.9 x 43.2 cm |
| Media Weight | Multipurpose Tray: 16 to 58 lb bond Trays 2 & 3: Up to 32 lb plain paper; 43 lb coated paper |
| Paper Capacity | Multipurpose Tray: 100 sheets Input Tray 2: 250 sheets Input Tray 3: 500 sheets Output Bin: 300 sheets Input Total: 850 sheets |
| Connectivity | USB 2.0 |
| Interface | 10/100/1000 Base-T Ethernet 2 x USB 2.0 host 2 x Internal USB host |
| Processor | 800 MHz |
| Memory | 1 GB |
| Printer Language | HP PCL 6, HP PCL 5, HP Postscript Level 3 emulation, native PDF printing (v1.4), Apple AirPrint |
| Mobile Printing Features | HP ePrint, Apple AirPrint |
| OS Support | Windows 8 (32/64-bit), 7 (32/64-bit), Vista (32/64-bit), XP SP2 or later (32/64-bit), Server 2012 (64-bit), Server 2008 (32/64-bit), Server 2008 R2 (64-bit), Server 2003 SP1 or later (32/64-bit) Mac OS X 10.6.8 and later iOS Android Citrix and Windows Terminal Services HP ePrint Linux, Novell SAP device types SAP Print UNIX UNIX Jetdirect |
| Network Protocols | IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall IPv6: DHCPv6, MLDv1, ICMPv6 IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print |
| Network Security | Management Security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication Support for WJA-10 IPsec Configuration using IPsec Plug-in |
| General Attributes | |
| Display | 2.0" / 5.2 cm 4-line Color Graphic Display (CGD) |
| Power Requirements | 110-127 VAC ($\pm 10\%$), 50/60 Hz (± 2 Hz) |
| Power Consumption | Printing (B&W): 677.41 W Printing (Color): 654.92 W Ready: 59.46 W Sleep: 9.09 W Off: 0.35 W |

| | |
|---|---|
| | Typical Electricity Consumption (TEC) Number: 3.68 kWh/week (3.053 kWh/week Blue Angel) |
| Certifications | Blue Angel ENERGY STAR |
| Safety Approvals | IEC 60950-1:2005 +A1; EN 60950-1: 2006 +A11:2009 +A1:2010 +A12:2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 (Class 1 Laser/ LED Product); UL/cUL Listed (USA/Canada); GS Certificate (Germany, Europe); IEC 62479:2010; EN 62479:2010; Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries |
| Electromagnetic Emission Certifications | CISPR 22:2008/EN 55022:2010 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 61000-3-3:2008; EN 55024:2010; FCC Title 47 CFR, Part 15 Class A(USA); ICES-003, Issue 4 (Canada); EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries |
| Acoustic Noise | Power Emissions: 6.7 B(A) Acoustic Power Emissions (Ready): 5.0 B(A) Acoustic Pressure Emissions Bystander (Active, Printing): 50 dB(A) Acoustic Pressure Emissions Bystander (Ready): 33 dB(A) |
| Operating Conditions | Temperature: 59 to 81°F / 15 to 27°C Recommended Temperature: 63 to 77°F / 17 to 25°C Humidity: 10 to 70%, relative Recommended Humidity: 30 to 70%, relative |
| Storage Conditions | Temperature: 32 to 95°F / 0 to 35°C Humidity: 10 to 90%, relative |
| Dimensions | 21.4 x 23 x 18" / 54.4 x 58.6 x 46.5 cm Max: 33 x 38.5 x 18" / 84 x 97.5 x 46.5 cm |
| Weight | 115.3 lb / 52.4 kg |
| Packaging Info | |
| Package Weight | 134.0 lb |
| Box Dimensions (LxWxH) | 29.0 x 28.5 x 28.0" |