

## HP Color LaserJet Enterprise M750dn Laser Printer



Rating: 4.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,424.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

### Description

**Item:** HEWD3L09A

**Part:** D3L09A#BGJ

**UPC:** 887758123294

### Performance

Printing Technology

Maximum Resolution

Print Speed

First Print Out Speed

Print Color

Laser; HP ImageREt 3600

600 x 600 dpi

30 ppm

10 seconds

CMYK

# Printers : HP Color LaserJet Enterprise M750dn Laser Printer

---

Duplex Printing	Automatic
Printer Duty Cycle	Up to 120,000 pages
Print Features	Recommended Monthly Volume: 2,500 to 13,000 pages HP ePrint, Open Extensibility Platform, FutureSmart Firmware, HP Easy Color, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs
Media Handling	Multipurpose tray
Paper Handling	Input tray 2 Input tray 3 Output bin
Paper Types	Paper (extra heavy, glossy, heavy, heavy glossy, high gloss images, intermediate, light, plain, recycle, tough), envelopes, labels, cardstock, transparencies
Paper Sizes	Multipurpose Tray: 3 x 5" / 7.6 x 12.7 cm, 4 x 6" / 10.2 x 15.2 cm, statement, 5 x 7" / 12.7 x 17.8 cm, 5 x 8" / 12.7 x 20.3 cm, letter, letter-R, legal, executive, 11 x 17" / 27.9 x 43.2 cm, 8.5 x 13" / 21.6 x 33 cm, 12 x 18" / 30.5 x 45.7 cm, #9/10/Monarch envelopes Trays 2 & 3: Letter, letter-R, legal, executive, 8.5 x 13" / 21.6 x 33 cm, 11 x 17" / 27.9 x 43.2 cm
Media Weight	Multipurpose Tray: 16 to 58 lb bond Trays 2 & 3: Up to 32 lb plain paper; 43 lb coated paper
Paper Capacity	Multipurpose Tray: 100 sheets Input Tray 2: 250 sheets Input Tray 3: 500 sheets Output Bin: 300 sheets Input Total: 850 sheets
Connectivity	USB 2.0
Interface	10/100/1000 Base-T Ethernet 2 x USB 2.0 host 2 x Internal USB host
Processor	800 MHz
Memory	1 GB
Printer Language	HP PCL 6, HP PCL 5, HP Postscript Level 3 emulation, native PDF printing (v1.4), Apple AirPrint
Mobile Printing Features	HP ePrint, Apple AirPrint
OS Support	Windows 8 (32/64-bit), 7 (32/64-bit), Vista (32/64-bit), XP SP2 or later (32/64-bit), Server 2012 (64-bit), Server 2008 (32/64-bit), Server 2008 R2 (64-bit), Server 2003 SP1 or later (32/64-bit) Mac OS X 10.6.8 and later iOS Android Citrix and Windows Terminal Services HP ePrint Linux, Novell SAP device types SAP Print UNIX UNIX Jetdirect
Network Protocols	<b>IPv4/IPv6:</b> Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall <b>IPv6:</b> DHCPv6, MLDv1, ICMPv6 <b>IPv4:</b> Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print
Network Security	Management Security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication Support for WJA-10 IPsec Configuration using IPsec Plug-in
General Attributes	
Display	2.0" / 5.2 cm 4-line Color Graphic Display (CGD)
Power Requirements	110-127 VAC ( $\pm 10\%$ ), 50/60 Hz ( $\pm 2$ Hz)
Power Consumption	Printing (B&W): 677.41 W Printing (Color): 654.92 W Ready: 59.46 W Sleep: 9.09 W Off: 0.35 W

	Typical Electricity Consumption (TEC) Number: 3.68 kWh/week (3.053 kWh/week Blue Angel)
Certifications	Blue Angel ENERGY STAR
Safety Approvals	IEC 60950-1:2005 +A1; EN 60950-1: 2006 +A11:2009 +A1:2010 +A12:2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 (Class 1 Laser/ LED Product); UL/cUL Listed (USA/Canada); GS Certificate (Germany, Europe); IEC 62479:2010; EN 62479:2010; Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries
Electromagnetic Emission Certifications	CISPR 22:2008/EN 55022:2010 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 61000-3-3:2008; EN 55024:2010; FCC Title 47 CFR, Part 15 Class A(USA); ICES-003, Issue 4 (Canada); EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries
Acoustic Noise	Power Emissions: 6.7 B(A) Acoustic Power Emissions (Ready): 5.0 B(A) Acoustic Pressure Emissions Bystander (Active, Printing): 50 dB(A) Acoustic Pressure Emissions Bystander (Ready): 33 dB(A)
Operating Conditions	Temperature: 59 to 81°F / 15 to 27°C Recommended Temperature: 63 to 77°F / 17 to 25°C Humidity: 10 to 70%, relative Recommended Humidity: 30 to 70%, relative
Storage Conditions	Temperature: 32 to 95°F / 0 to 35°C Humidity: 10 to 90%, relative
Dimensions	21.4 x 23 x 18" / 54.4 x 58.6 x 46.5 cm Max: 33 x 38.5 x 18" / 84 x 97.5 x 46.5 cm
Weight	115.3 lb / 52.4 kg
Packaging Info	
Package Weight	134.0 lb
Box Dimensions (LxWxH)	29.0 x 28.5 x 28.0"