

HP DesignJet T1300 44in Postscript Printer



Rating: 3.0
Price:
Variant price modifier:

Price with discount:
Salesprice with discount:
USD 3,497.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

Item: CR652A
UPC: 886111279982

Printer
Printing Technology
Print Speed

Print Resolution

Ink Palette
Ink Types

Ink Droplet Size

Line Accuracy
Line Width

HP Thermal Inkjet
Line Drawings: 28 sec/page on A1/D (103 A1/D prints/hour)
Color Images - Fast: 445 ft2/hr (41 m2/hr) on coated media
Color Images - Best: 33.3 ft2/hr (3.1 m2/hr) on glossy media
Input dpi: 1200 x 1200 dpi
Optimized dpi: 2400 x 1200 dpi
Cyan, Gray, Magenta, Matte Black, Photo Black, Yellow
Dye-Based: Cyan, Gray, Magenta, Photo Black, Yellow
Pigment-Based: Matte Black
6 pl: Cyan, Gray, Magenta, Photo Black
9 pl: Matte Black, Yellow
±0.1%
Minimum Line Width: 0.0008" (0.02 mm)

Printers : HP DesignJet T1300 44in Postscript Printer

Maximum Optical Density	Guaranteed Minimum: 0.0024" (0.06 mm)
Hard Disk Capacity	2.15 (black)
Memory	160 GB
Paper Handling	32 GB (virtual)
Paper-Feed Method	Sheet feed, two automatic roll feeds, automatic roll-switching, automatic cutter
Media Types	Bond & Coated Paper: Bond, Coated, Heavyweight Coated, Super Heavyweight Plus Matte Technical Paper: Natural Tracing, Translucent Bond, Vellum Film: Clear, Matte Photographic Paper: Satin, Gloss, Semi-Gloss, Matte, High-Gloss Self-Adhesive: Polypropylene, Vinyl
Media Weight	60 to 328 g/m2
Media Thickness	Up to 31.5 mil (0.8 mm)
Paper Sizes	Sheets: 8.26 x 11.0 to 44.0 x 66.0" (210 x 279 to 1118 x 1676 mm) Rolls: 11.0 to 44" (279 to 1118 mm)
Maximum Printable Length	300' (91.44 m)
Roller Diameter	Up to 5.3" (13.46 cm)
Margins	Roll: 0.2 x 0.2 x 0.2 x 0.2" (5.0 x 5.0 x 5.0 x 5.0 mm) (borderless on photo papers) Sheet: 0.2 x 0.67 x 0.2 x 0.2" (5.0 x 17.0 x 5.0 x 5.0 mm)
Connectivity	Hi-Speed USB 2.0 certified
Interface	Gigabit Ethernet (1000Base-T) EIO Jetdirect accessory slot
Printer Language	Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI
Drivers	HP-GL/2, HP-RTL drivers for Windows (optimized for AutoCAD 2000 and higher), HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers
OS Compatibility	Microsoft: Windows 7 (Ultimate, Professional, Home Premium), Vista (Ultimate, Business, Home Premium), XP 32-bit & 64-bit (Professional, Home), Windows Server 2008 (32-bit, 64-bit), Server 2003 (32-bit, 64-bit) Mac: OS X v 10.5, v 10.6 Citrix: XenApp, XenServer
Windows System Requirements	Windows XP: SP2 or later, Intel Pentium or AMD K6/Athlon/Duron (1 GHz), 1 GB RAM, 2 GB available hard disk space Windows Vista: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space OS X v 10.4, 10.5: PowerPC G4, G5, or Intel Core Processor, 1 GB RAM, 2 GB available hard disk space
Mac System Requirements	
General Attributes	
Power Requirements	100 to 240 VAC (±10%), 50/60 Hz (±3 Hz), 2 A max
Power Consumption	Printing: < 120 Watts Powersave: < 7 Watts (Off: 0.1 Watts
Certifications	Safety: USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE) Electromagnetic: Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental: WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP
Acoustics	Sound Pressure- Active: 46 dB(A) Sound Pressure- Standby: 29 dB(A) Sound Power - Active: 6.3 B(A) Sound Power - Standby: 4.4 B(A)
Temperature / Humidity	Operating Temperature: 41 to 104 °F (5 to 40 °C) Storage Temperature: -13 to 131 °F (-25 to 55 °C) Operating Humidity: 20 to 80%
Dimensions (WxDxH)	Printer: 69.7 x 28.4 x 41.3" (177.0 x 72.1 x 105.0 cm) Shipping: 76.0 x 30.2 x 30.3" (193.0 x 76.6 x 77.0 cm)
Weight	Printer: 189 lb (86 kg) Shipping: 240 lb (109 kg)
Packaging Info	
Package Weight	265.0 lb
Box Dimensions (LxWxH)	69.7 x 41.3 x 28.4"

