

## HP DesignJet T2530 36in PostScript Multifunction Printer



Rating: 4.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 4,747.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

### Description

**Item:** L2Y26A

**UPC:** 889296106357

Printing Method

Printing Technology

Maximum Resolution

Print Speed

Ink Type

HP Thermal Inkjet

Up to 2400 x 1200 optimized dpi

Print Time Line Drawing: 21 sec/page on A1/D (economode)

Print Speed Line Drawing: 120 A1/D prints per hour (economode)

Dye-based: C, G, M, pK, Y

Pigment-based: mK

# Printers : HP DesignJet T2530 36in PostScript Multifunction Printer

---

Ink Droplet Size	C, M, Y, G, pK: 6 pL mK: 9 pL
Ink Cartridge Configuration	6 x Cartridges: cyan, gray, magenta, matte black, photo black, yellow
Ink Cartridge Capacity	130 or 300 mL
Margins	Top x Bottom x Left x Right: Roll: 0.12 x 0.12 x 0.12 x 0.12" (3 x 3 x 3 x 3 mm) Sheet: 0.12 x 0.87 x 0.12 x 0.12" (3 x 22 x 3 x 3 mm) ±0.1%
Line Accuracy	±0.1%
Printhead	C, G, M, mK, pK, Y
Minimum Line Width	0.8 mil (0.02 mm) (HP-GL/2 addressable)
Guaranteed Minimum Line Width	2.8 mil (0.07 mm) (ISO/IEC 13660:2001(E))
Maximum Optical Density	Black: 2.15 D (6 L* min)
Applications	Line drawings, renderings, presentations, maps, orthophotos
Memory	128 GB (file processing)
Hard Disk	500 GB
Media Types & Handling	
Paper Handling	Input: two automatic front-loading roll feeds, smart roll switching, sheet feed Output: integrated output stacking tray (from A4/A to AO/E, with up to 50 A1/D-size capacity), media bin, automatic cutter
Paper Types	Bond and coated paper (bond, coated, heavyweight coated, super heavyweight plus matte, colored), technical paper (natural tracing, translucent bond, vellum), film (clear, matte, polyester), photographic paper (satin, gloss, semi-gloss, matte, high-gloss), backlit, self-adhesive (two-view cling, indoor paper, polypropylene, vinyl)
Media Sizes	Standard: Rolls: 11 to 36" (27.9 to 91.4 cm) Sheets: 8.3 x 11 to 36 x 48" (21 x 27.9 to 91.4 x 121.9 cm) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E)  Custom: 8.3 x 11 to 36 x 48" (21 x 27.9 to 91.4 x 121.9 cm) External Diameter: 5.5" (14 cm) Up to 19.7 mil (0.5 mm)
Roll	
Media Thickness	
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T) USB 2.0
Printer Language	Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP-PCL3GUI, URF
Printing Paths	Direct printing from USB flash drive, email printing, HP driver for Windows, HP driver for Mac OS X, HP Print Service for Android, Apple AirPrint driver
Drivers	Included: HP-GL/2, HP-PCL3GUI drivers for Windows and Mac OS X; PostScript drivers for Windows, Linux, and Mac OS X
Scanner	
Scanner Type	Sheetfed, CIS (Contact Image Sensor)
Scan Speed	Color: Up to 2.5 in/sec (6.35 cm/sec) Grayscale: Up to 7.5 in/sec (19.05 cm/sec) Up to 600 dpi
Scan Resolution	
Paper Handling	Straight-through scan paper path for sheet and cardboard originals
Maximum Scan Size	JPEG: 36 x 315" (91.4 x 800 cm) () PDF: 36 x 197" (91.4 x 500 cm) () TIFF: 24 x 590.5" (61 x 1,500 cm) () Up to 1.2 mil (0.03 in)
Thickness	
Copier	
Reduction / Enlargement	25 to 400%
Number of Copies	Up to 99 copies
Copier Settings	Copy quality, copy color, roll, content type, original paper type, background removal, contrast, de-skew, blueprints support
Physical	
Temperature	Operating: 41 to 104°F (5 to 40°C) Storage: -13 to 131°F (-25 to 55°C)
Operating Humidity	20 to 80% RH
Acoustic Noise	Sound Pressure: 47 dB(A) (printing); 39 dB(A) (ready); Sound Power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)
Power Consumption	Printing: 120 W Sleep: 1.3 W (5 W with embedded Digital Front End) Auto Ranging: 100 to 240 VAC (±10%), 50/60 Hz (±3 Hz)
Input Voltage	
Input Current	2 A maximum
Certifications	Safety:

USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant),  
Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM),  
Mexico (NYCE), Korea (KATS)

Electromagnetic:

Compliant with Class A requirements, including: USA (FCC rules),  
Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand  
(RSM), China (CCC), Japan (VCCI); Certified as Class A product:  
Korea (KCC)

Environmental:

ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EPEAT  
Bronze

Dimensions (WxDxH)

55.1 x 36.1 x 43.7" (139.9 x 91.6 x 111 cm)

Weight

245 lb (112 kg)