

## HP DesignJet T790 24in ePrinter



Rating: 3.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,800.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

**Item:** CR648AB1K

**UPC:** 886111274611

Printing Method

Printing Technology

Maximum Resolution

Minimum Ink Droplet Size

Ink Type

Thermal inkjet

1200 dpi (optimized: 2400 x 1200 dpi)

**Cyan, Gray, Magenta, Photo Black:** 6 pl

**Matte Black, Yellow:** 9 pl

**Cyan, Gray, Magenta, Photo Black, Yellow:** dye-based

Ink Palette	<b>Matte Black:</b> pigment-based Cyan, gray, magenta, matte black, photo black, yellow
Ink Cartridge Configuration	6 individual ink cartridges, 3 Printheads (gray & photo black, matte black & yellow, magenta & cyan)
Line Accuracy	±0.1%
Performance	<b>Normal:</b> 93 D prints per hour
Print Speed	<b>Line Drawing:</b> 72 D prints per hour <b>Best Drawing:</b> 30 ft <sup>2</sup> /hr <b>Image Draft</b> 400 ft <sup>2</sup> /hr
Paper Handling	24.0" (610 mm)
Maximum Paper Width	24.0" x 300.0' (610 mm x 91.44 m)
Maximum Printable Area	<b>Sheet:</b> 0.2 x 0.67 x 0.2 x 0.2" (5 x 17 x 5 x 5 mm)
Margins	<b>Roll:</b> 0.2 x 0.2 x 0.2 x 0.2" (5 x 5 x 5 x 5 mm)
Paper Sizes	<b>Sheet:</b> 8.26 x 11.0 to 24.0 x 66.0" (210 x 279 to 610 x 1676 mm )
Paper Types	<b>Roll:</b> 11.0 to 24.0" (279 to 610 mm) rolls <b>Bond And Coated Paper:</b> bond, coated, heavyweight coated, super heavyweight plus matte <b>Technical Paper:</b> natural tracing, translucent bond, vellum <b>Film:</b> clear, matte <b>Photographic Paper:</b> satin, gloss, semi-gloss, matte, high-gloss <b>Self-Adhesive:</b> polypropylene, vinyl Technical paper, film, self-adhesive paper
Special Media Support	60 to 328 g/m <sup>2</sup>
Media Weight	Up to 0.8 mm (31.5 mil)
Media Thickness	5.3" (134.62 mm) external diameter
Maximum Media Roll Diameter	300.0' (91 m)
Maximum Roll Print Length	Sheet feed, roll feed, automatic cutter
Paper-Feed Method	Fast Ethernet (100Base-T), Hi-Speed USB 2.0 certified, EIO Jetdirect accessory slot
Connectivity	Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI
Computer Interface	HP-GL/2, HP-RTL drivers for Windows (optimized for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers
Printer Language	Fast Ethernet (100Base-T)
Drivers	<b>Microsoft:</b> Windows 7 Ultimate/Professional/Home Premium, Windows Vista Ultimate/Business/Home Premium, Windows XP (32-bit, 64-bit) Professional/Home, Windows Server 2008 (32-bit, 64-bit), Windows Server 2003 (32-bit, 64-bit)
Network Capable	<b>Mac:</b> OS X v 10.5, v 10.6
OS Compatibility	<b>Citrix:</b> XenApp, XenServer <b>Linux</b>
Windows System Requirements	<b>Windows XP:</b> (SP2 or later) Intel Pentium family or AMD K6/Athlon/Duron family (1 GHz) 1 GB RAM 2 GB available hard disk space <b>Windows Vista:</b> 32-bit (x86) or 64-bit (x64) processor (1 GHz) 2 GB RAM 2 GB available hard disk space
Apple System Requirements	OS X v 10.4, OS X v 10.5 PowerPC G4, G5, or Intel Core Processor 1 GB RAM 2 GB available hard disk space
Environmental	<b>Operating Temperature:</b> 41 to 104 °F (5 to 40 °C)
Temperature	<b>Storage Temperature:</b> -13 to 131 °F (-25 to 55 °C )
Humidity	<b>Operating Humidity:</b> 20 to 80% RH <b>Storage Humidity:</b> 0 to 95% RH
Acoustic Noise	<b>Sound Pressure:</b> active - 46 dB(A); standby - 29 dB(A) <b>Sound Power:</b> active - 6.3 B(A); standby - 4.4 B(A)
Physical	8.0 GB
Buffer/Ram	160 GB
Hard Drive Space	<b>Printing:</b> < 120 Watts
Power Consumption	<b>Powersave:</b> < 7 Watts <b>Off:</b> 0.1 Watts

## Printers : HP DesignJet T790 24in ePrinter

---

Power Requirements	100 to 240 VAC ( $\pm 10\%$ ), 50/60 Hz ( $\pm 3$ Hz), 2 A max
Dimensions	49.7 x 27.6 x 41.3" (1262 x 702 x 1050 mm)
Weight	132.0 lb (60.0 kg)
Packaging Info	
Package Weight	190.0 lb
Box Dimensions (LxWxH)	56.2 x 30.1 x 24.0"