

## HP DesignJet T795 44in ePrinter



Rating: 4.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,697.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

**Item:** CR649C

Printing Method

Printing Technology

Maximum Resolution

Print Speed

HP Thermal Inkjet

Color: 2400 x 1200 dpi

Line Drawings: 28 sec/page on A1/D; 103 A1/D prints/hr

Ink Type	Color, Fast: 445 ft <sup>2</sup> /hr (41 m <sup>2</sup> /hr) on coated media Color, Best: 33.3 ft <sup>2</sup> /hr (3.1 m <sup>2</sup> /hr) on glossy media Dye-Based: Cyan, magenta, yellow, dark gray, gray Pigment-Based: Matte black
Ink Droplet Sizes	6 pl: Cyan, magenta, photo black, gray 9 pl: Yellow, matte black
Ink Cartridge Configuration Compatible Ink Cartridges	6: Cyan, magenta, yellow, photo black, gray, and matte black HP 72 HP 726
Printhead Minimum Line Width	3 (Gray & photo black, matte black & yellow, magenta & cyan) 0.0024" (0.06 mm) (ISO/IEC 13660:2001(E)) 0.0008" (0.02 mm) (HP-GL/2 addressable)
Line Accuracy Maximum Optical Density Paper Handling Paper-Feed Method	±0.1% 6 L*min/2.15 D  Sheet feed Roll feed
Paper Sizes	Roll: 8.3 to 44.0" (21.0 to 111.8 cm) wide and up to 5.3" (13.5 cm) in diameter Sheets: 8.3 x 11.0" to 44.0 x 66.0" (21.0 x 27.9 cm to 111.8 x 167.6 cm); A4, A3, A2, A1, A0 (A, B, C, D, E)
Media Thickness Media Weight Margins	Up to 31.5 mil (0.8 mm) 60-328 gsm Sheet: 0.20 x 0.67 x 0.20 x 0.20" (5 x 17 x 5 x 5 mm) Roll: 0.2 x 0.2 x 0.2 x 0.2" (5 x 5 x 5 x 5 mm)
Paper Handling Applications Connectivity Interfaces	Automatic cutter Line drawings, rendering, presentations  1000Base-T Gigabit Ethernet port USB 2.0 port EIO Jetdirect accessory slot
Memory Hard Disk Drive Printer Language	16 GB (virtual) 160 GB, optional Standard: HP-GL/2, HP-RTL, CALS G4, TIFF, JPEG, HP PCL 3 GUI Optional: Adobe PostScript 3, Adobe PDF 1.7
PostScript Support Printing Paths	Adobe PostScript 3 Printer driver, HP Designjet ePrint & Share, Direct printing from USB flash drive, email printing
Drivers	HP-GL/2, HP-RTL drivers for Windows, HP PCL 3 GUI drive for Mac OS X, PostScript Windows and Mac OS X drivers with optional PostScript/PDF Upgrade Kit
Physical LCD Power Requirements Power Consumption Certifications	Touchscreen Auto Ranging: 100 to 240 VAC (±10%), 50/60 Hz(±3 Hz), 2 A max Printing: Ready: Sleep: Off: <0.1 W <b>Safety:</b> USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KC) <b>Electromagnetic:</b> Compliant with Class A requirements, including: USA (FCC), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (MSIP) <b>Environmental:</b> ENERGY STAR, WEEE, RoHS (EU, China, Korea, India), REACH, EPEAT Bronze, FEMP
Acoustic Noise	<b>Sound Pressure</b> Active: 43 dB(A) Standby: 29 dB(A)  <b>Sound Power</b> Active: 6.1 B(A) Standby: 4.7 B(A)
Temperature / Humidity	Operating Temperature: 41 to 104°F (5 to 40°C) Storage Temperature: -13 to 131°F (-25 to 55°C) Operating Humidity: 20 to 80%, relative
Dimensions (WxDxH) Weight Packaging Info Package Weight Box Dimensions (LxWxH)	69.7 x 27.6 x 41.3" (177.0 x 70.1 x 105.0 cm) 180 lb (82 kg)  227.0 lb 76.0 x 30.0 x 30.0"

