

HP DesignJet T795 44in ePrinter



Rating: 4.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,697.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

Item: CR649C

Printing Method

Printing Technology

Maximum Resolution

Print Speed

HP Thermal Inkjet

Color: 2400 x 1200 dpi

Line Drawings: 28 sec/page on A1/D; 103 A1/D prints/hr

<p>Ink Type</p> <p>Ink Droplet Sizes</p> <p>Ink Cartridge Configuration</p> <p>Compatible Ink Cartridges</p> <p>Printhead</p> <p>Minimum Line Width</p> <p>Line Accuracy</p> <p>Maximum Optical Density</p> <p>Paper Handling</p> <p>Paper-Feed Method</p> <p>Paper Sizes</p> <p>Media Thickness</p> <p>Media Weight</p> <p>Margins</p> <p>Paper Handling</p> <p>Applications</p> <p>Connectivity</p> <p>Interfaces</p> <p>Memory</p> <p>Hard Disk Drive</p> <p>Printer Language</p> <p>PostScript Support</p> <p>Printing Paths</p> <p>Drivers</p> <p>Physical</p> <p>LCD</p> <p>Power Requirements</p> <p>Power Consumption</p> <p>Certifications</p> <p>Acoustic Noise</p> <p>Temperature / Humidity</p> <p>Dimensions (WxDxH)</p> <p>Weight</p> <p>Packaging Info</p> <p>Package Weight</p> <p>Box Dimensions (LxWxH)</p>	<p>Color, Fast: 445 ft²/hr (41 m²/hr) on coated media Color, Best: 33.3 ft²/hr (3.1 m²/hr) on glossy media Dye-Based: Cyan, magenta, yellow, dark gray, gray Pigment-Based: Matte black</p> <p>6 pl: Cyan, magenta, photo black, gray 9 pl: Yellow, matte black</p> <p>6: Cyan, magenta, yellow, photo black, gray, and matte black HP 72 HP 726</p> <p>3 (Gray & photo black, matte black & yellow, magenta & cyan) 0.0024" (0.06 mm) (ISO/IEC 13660:2001(E)) 0.0008" (0.02 mm) (HP-GL/2 addressable) ±0.1%</p> <p>6 L*min/2.15 D</p> <p>Sheet feed Roll feed</p> <p>Roll: 8.3 to 44.0" (21.0 to 111.8 cm) wide and up to 5.3" (13.5 cm) in diameter Sheets: 8.3 x 11.0" to 44.0 x 66.0" (21.0 x 27.9 cm to 111.8 x 167.6 cm); A4, A3, A2, A1, A0 (A, B, C, D, E) Up to 31.5 mil (0.8 mm)</p> <p>60-328 gsm Sheet: 0.20 x 0.67 x 0.20 x 0.20" (5 x 17 x 5 x 5 mm) Roll: 0.2 x 0.2 x 0.2 x 0.2" (5 x 5 x 5 x 5 mm)</p> <p>Automatic cutter Line drawings, rendering, presentations</p> <p>1000Base-T Gigabit Ethernet port USB 2.0 port EIO Jetdirect accessory slot 16 GB (virtual) 160 GB, optional Standard: HP-GL/2, HP-RTL, CALS G4, TIFF, JPEG, HP PCL 3 GUI Optional: Adobe PostScript 3, Adobe PDF 1.7 Adobe PostScript 3 Printer driver, HP Designjet ePrint & Share, Direct printing from USB flash drive, email printing</p> <p>HP-GL/2, HP-RTL drivers for Windows, HP PCL 3 GUI drive for Mac OS X, PostScript Windows and Mac OS X drivers with optional PostScript/PDF Upgrade Kit</p> <p>Touchscreen Auto Ranging: 100 to 240 VAC (±10%), 50/60 Hz(±3 Hz), 2 A max Printing: Ready: Sleep: Off: <0.1 W Safety: USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KC) Electromagnetic: Compliant with Class A requirements, including: USA (FCC), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (MSIP) Environmental: ENERGY STAR, WEEE, RoHS (EU, China, Korea, India), REACH, EPEAT Bronze, FEMP</p> <p>Sound Pressure Active: 43 dB(A) Standby: 29 dB(A)</p> <p>Sound Power Active: 6.1 B(A) Standby: 4.7 B(A)</p> <p>Operating Temperature: 41 to 104°F (5 to 40°C) Storage Temperature: -13 to 131°F (-25 to 55°C) Operating Humidity: 20 to 80%, relative 69.7 x 27.6 x 41.3" (177.0 x 70.1 x 105.0 cm) 180 lb (82 kg)</p>
---	--

