

HP DesignJet T920 36in PostScript ePrinter



Rating: 5.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,299.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

Item: CR355AB1K

Printing Method

Printing Technology

Maximum Resolution

Print Speed

Ink Droplet Sizes

Thermal inkjet

2400 x 1200 optimized dpi from 1200 x 1200 input dpi (black, color)

D Color Line Drawing: 21 seconds / page, 120 prints / hour (draft)

D Black Line Drawing: 120 prints / hour (draft)

6.0 pl: Cyan, magenta, yellow, gray, photo black

9.0 pl: Matte black

Ink Palette	Cyan, gray, magenta, matte black, photo black, yellow
Ink Type	Dye-Based: Cyan, gray, magenta, photo black, yellow Pigment-Based: Matte black
Ink Cartridge Configuration	6 cartridges, 1 printhead
Compatible Ink Cartridges	727 Photo Black Ink Cartridge (40 ml) 727 Photo Black Ink Cartridge (130 ml) 727 Matte Black Ink Cartridge (69 ml) 727 Matte Black Ink Cartridge (130 ml) 727 Matte Black Ink Cartridge (300 ml) 727 Cyan Ink Cartridge (40 ml) 727 Cyan Ink Cartridge (130 ml) 727 Magenta Ink Cartridge (40 ml) 727 Magenta Ink Cartridge (130 ml) 727 Yellow Ink Cartridge (40 ml) 727 Yellow Ink Cartridge (130 ml) 727 Gray Ink Cartridge (40 ml) 727 Gray Ink Cartridge (130 ml)
Line Width	Minimum: 0.8 mil (0.02 mm) Guaranteed Minimum: 2.8 mil (0.07 mm)
Line Accuracy	±0.1%
Maximum Optical Density	2.15 maximum black optical density (6 L*min)
Paper Handling	
Paper-Feed Method	Automatic front-loading roll feed Sheet feed
Finishing	Integrated output stacking tray (A4/A to A0/E; 50x A1/D sheets) Basket Automatic cutter
Paper Sizes	Sheet: 8.3 x 11.0 to 36.0 x 66.0" (21.0 x 27.94 to 91.44 x 167.64 cm) Roll Width: 11.0 to 36.0" (27.94 to 91.44 cm)
Maximum Roll Print Length	300' (91.44 m)
Maximum Media Roll Diameter	5.5" (13.97 cm)
Non-Printable Area	Roll: 0.2 x 0.2 x 0.2 x 0.2" (5.0 x 5.0 x 5.0 x 5.0 mm) Sheet: 0.2 x 0.87 x 0.2 x 0.2" (5.0 x 22.0 x 5.0 x 5.0 mm)
Media Weight	60 to 328 g/m2
Media Thickness	Up to 11.8 mil (0.3 mm)
Media Types	Bond / Coated: Bond, coated, heavyweight coated, super heavyweight plus matte, colored Technical: Natural tracing, translucent bond, vellum Film: Clear, matte, polyester Photo: Satin, gloss, semi-gloss, matte, high-gloss Backlit Self-Adhesive: Two-view cling, indoor paper, polypropylene, vinyl
Connectivity	
Interfaces	Hi-Speed USB 2.0 (host) Gigabit Ethernet (1000Base-T)
OS Compatibility	Windows: Windows 8 Professional / Home (32 / 64-bit), Windows 7 Ultimate / Professional / Home Premium (32 / 64-bit), Vista Ultimate / Business / Home Premium (32 / 64-bit), XP Professional / Home (32 / 64-bit), Server 2012, Server 2008 (32 / 64-bit), Server 2008 R2, Server 2003 (32 / 64-bit) Mac: OS X 10.6, 10.7, 10.8 Linux
Internal Memory	Physical DRAM: 1.5 GB Virtual Memory: 32 GB
Printer Language	HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF
Print Drivers	HP-GL/2, HP-RTL drivers for Windows HP PCL 3 GUI driver for Mac OS X PostScript Windows, Linux, and Mac drivers
Physical	
Power Requirements	100 to 240 VAC (±10%), 50 / 60 Hz (±3.0 Hz), 4.2 A max
Power Consumption	Printing: < 120 watt Maximum: < 260 watt Sleep: < 4.0 watt (< 7.0 watt with embedded Digital Front End) Auto-Off: 0.1 watt Manual Off: 0 watt
Certifications	Safety: CSA (USA / Canada), LVD and EN60950-1 (EU), GOST (Russia), PSB (Singapore), CCC (China), IRAM (Argentina), NYCE (Mexico), KATS (Korea) Electromagnetic Class B requirements, including: FCC rules (USA),

Acoustic Noise	ICES (Canada), EMC Directive (EU), ACMA (Australia), RSM (New Zealand), CCC (China), VCCI (Japan) Class A product KCC (Korea) Environmental: Energy Star, WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP Sound Pressure (Printing): 47 dB(A) Sound Pressure (Ready): 39 dB(A) Sound Pressure (Sleep): < 16 dB(A) Sound Power (Printing): 6.5 B(A) Sound Power (Ready): 5.8 B(A) Sound Power (Sleep): < 1.9 B(A)
Temperature / Humidity	Operating Temperature: 41 to 104°F (5 to 40°C) Recommended: 59 to 95°F (15 to 35°C) depending on paper type Storage temperature: -13 to 131°F (-25 to 55°C) Recommended Operating Humidity: 20 to 80%, depending on paper type
Dimensions (WxDxH)	Storage Humidity: 0 to 95% Maximum: 55.08 x 36.1 x 43.7" (1399 x 916 x 1110 mm) Minimum: 55.08 x 27.3 x 37.4" (1399 x 693 x 950 mm)
Weight	192 lb (87 kg)
Packaging Info	
Package Weight	191.8 lb
Box Dimensions (LxWxH)	55.1 x 37.4 x 27.3"