

JVC GY-HM620 ProHD Mobile News Camera



Rating: 4.0
Price:
Variant price modifier:

Price with discount:
Salesprice with discount:
USD 1,497.00
Discount:

 [Ask a question about this product](#)
Manufacturer: [JVC](#)

Description
Product Highlights

Camcorder : JVC GY-HM620 ProHD Mobile News Camera

• Three 1/3" 12-Bit CMOS Sensors • Full HD Up to 60p/ Records SD Video • Integrated Fujinon 23x Optical Zoom Lens • Supports .MOV, .MP4, and AVCHD 2.0 • HDMI, HD-SDI Output, 2x XLR Audio Inputs	
Sensor	1/3" 2.2M pixels progressive scan 3CMOS
Synchronizing System	Internal
Stabilizer	Optical image stabilizer
Lens	Fujinon F1.6-3.0, 23x, f=4.1 - 94.3 mm (35 mm conversion: 29 to 667 mm)
Filter Diameter	72 mm
Shutter Speed	1/6 to 1/10000
Gain	-6, -3, 0, 3, 6, 9, 12, 15, 18 dB, Lolux, AGC
ND Filter	1/4, 1/16, 1/64
LCD Display	3.5" (8.9 cm) 920K pixels, 16:9
Viewfinder	LCOS: 0.45" (1.1 cm) 1.22M pixels, 16:9
Recording Media	2x SDHC/SDXC memory card class 6/10
Video Recording	Video codec: MPEG2 Long GOP (HD), AVCHD, H.264 (SD) File format: MOV (HD/SD: H.264), MP4 (XDCAM EX), MTS (AVCHD)
Recording Mode	MPEG-2 Long GOP: NTSC setting -- HQ mode: 1920 x 1080/59.94i, 29.97p, 23.98p, 1440 x 1080/59.94i, 1280 x 720/59.94p, 29.97p, 23.98p SP mode: 1440 x 1080/59.94i PAL setting -- HQ mode: 1920 x 1080/50i, 25p, 1440 x 1080/50i SP mode: 1440 x 1080/50i AVCHD NTSC setting -- HQ mode: 1920 x 1080/59.94i, SP mode: 1920 x 1080/59.94i PAL setting -- HQ mode: 1920 x 1080/50i, SP mode: 1920 x1080/50i SD (H.264) NTSC setting: 720 x 480/59.94i Proxy (H.264) NTSC setting: LP/LV mode: 480 x 270/29.97p, 23.98p PAL setting: LP/LV mode: 480 x 270/25p Records 4:2:0 but has a live output of 4:2:2 LPCM 2ch, 48kHz/16-bit (MPEG-2 Long GOP/H.264), AC3 (AVCHD) (1) AV output (f3.5 mm mini jack) (1) SDI output (1) HDMI output (2) XLR (MIC, +48V/LINE) (1) f3.5 mm mini jack (1) AV output (f3.5 mm mini jack) (1) f3.5 mm mini jack (1) RCA (1) f2.5 mm mini jack 32 to 104°F (0 to 40°C) 14 to 122°F (-20 to 50°C) 35 to 80% Under 85% DC 12V (AC adapter), DC 7.2V (battery) Approx. 12W (with VF and LCD monitor) 7 x 7.8 x 16.3" (17.8 x 19.8 x 41.6 cm) Approx. 5.3 lbs (2.4 kg) 9.05 lb 19.8 x 11.5 x 10.6"
Sampling	
Audio Recording	
Video Output	
Audio Input	
Audio Output	
Headphone	
Time Code Link Input/Output	
Remote	
Operating Temperature	
Storage Temperature	
Operating Humidity	
Storage Humidity	
Power	
Power Consumption	
Dimensions	
Weight	
Packaging Info	
Package Weight	
Box Dimensions (LxWxH)	