

JVC GY-HM660 ProHD Mobile News Streaming Camera



Rating: 5.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,724.00

Discount:



[Ask a question about this product](#)

Manufacturer: [JVC](#)

Description

Product Highlights

- Three 1/3" 12-Bit CMOS Sensors
- Full HD Up to 60p/ Records SD Video
- Integrated Fujinon 23x Optical Zoom Lens
- Supports .MOV, .MP4, and AVCHD 2.0
- HDMI, HD-SDI Output, 2x XLR Audio Inputs
- Dual Codec Recording
- Zixi, SMPTE2022, and RTMP Streaming
- Simultaneously Record and Stream
- In-Camera Clip Trimming
- IFB Audio Channel

Sensor

Synchronizing System

Stabilizer

Lens

Filter Diameter

Shutter Speed

Gain

ND Filter

LCD Display

Viewfinder

Recording Media

Video Recording

Recording Mode

1/3" 2.2M pixels progressive scan 3CMOS

Internal

Optical image stabilizer

Fujinon F1.6-3.0, 23x, f=4.1 - 94.3 mm (35 mm conversion: 29 to 667 mm)

72 mm

1/6 to 1/10000

-6, -3, 0, 3, 6, 9, 12, 15, 18 dB, Lolux, AGC

1/4, 1/16, 1/64

3.5" (8.9 cm) 920K pixels, 16:9

LCOS: 0.45" (1.1 cm) 1.22M pixels, 16:9

2x SDHC/SDXC memory card class 6/10

Video codec: MPEG2 Long GOP (HD), AVCHD, H.264 (SD)

File format: MOV (HD/SD: H.264), MP4 (XDCAM EX), MTS (AVCHD)

MPEG-2 Long GOP:

NTSC setting --

HQ mode: 1920 x 1080/59.94i, 29.97p, 23.98p, 1440 x 1080/59.94i,

1280 x 720/59.94p, 29.97p, 23.98p

SP mode: 1440 x 1080/59.94i

PAL setting --

HQ mode: 1920 x 1080/50i, 25p, 1440 x 1080/50i

SP mode: 1440 x 1080/50i

AVCHD

NTSC setting --

HQ mode: 1920 x 1080/59.94i, SP mode: 1920 x 1080/59.94i

PAL setting --

HQ mode: 1920 x 1080/50i, SP mode: 1920 x 1080/50i

SD (H.264)

NTSC setting: 720 x 480/59.94i

Proxy (H.264)

NTSC setting: LP/LV mode: 480 x 270/29.97p, 23.98p

PAL setting: LP/LV mode: 480 x 270/25p

Records 4:2:0 but has a live output of 4:2:2

LPCM 2ch, 48kHz/16-bit (MPEG-2 Long GOP/H.264), AC3 (AVCHD)

(1) AV output (f3.5 mm mini jack)

(1) SDI output

(1) HDMI output

(2) XLR (MIC, +48V/LINE)

(1) f3.5 mm mini jack

(1) AV output (f3.5 mm mini jack)

(1) f3.5 mm mini jack

(1) RCA

(1) f2.5 mm mini jack

32 to 104°F (0 to 40°C)

14 to 122°F (-20 to 50°C)

35 to 80%

Under 85%

DC 12V (AC adapter), DC 7.2V (battery)

Approx. 12W (with VF and LCD monitor)

7 x 7.8 x 16.3" (17.8 x 19.8 x 41.6 cm)

Approx. 5.3 lbs (2.4 kg)

Sampling

Audio Recording

Video Output

Audio Input

Audio Output

Headphone

Time Code Link Input/Output

Remote

Operating Temperature

Storage Temperature

Operating Humidity

Storage Humidity

Power

Power Consumption

Dimensions

Weight