

## Mutoh ValueJET 1324 Large Format Color Printer ValuePrint & Cut Package



Rating: 4.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 7,747.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Mutoh](#)

Description

### ValueJet 1324 ValuPrint & Cut Package Contents:

- ValueJET 1324 54" Printer
- Vinyl Express Q54 54" w/ARMS Vinyl Cutter
- 220 ml Eco Ultra Ink Starter Kit for ValueJET 1324
- FlexiSIGN & PRINT 12 Software
- Crossover Cable
- Basic One Year On-Site Warranty
- Initial 90-Day Premium Support

### Mutoh ValueJet 1324 54" Printer Specifications

Printer Technology	Drop on demand Micro Piezo Inkjet Technology, 4 - Color Print Head: C,M,Y,K
Maximum Media Width	54"
Maximum Print Width	53.6" (Bi-D), 53.35" (Uni-D)
Print Speed	Up to 565 sq ft/hr
Multiple Print Modes / Resolutions	1440/720/360 DPI: 12 modes (resolutions and passes)
Ink Type	Eco Ultra Ink
Ink Color	4 Colors (C,M,Y,K)

Ink Supply	Ink Cartridge Supply System
Ink Cartridge Capacity	220ml
Number of Cartridges	4
Spectrophotometer port	Standard (SPECTROVUE VM-10 optional)
Interface	Ethernet 10/100 Base-TX
Memory	128MB
Maximum Roll Media Weight / Diameter	42lbs   3 inch Scroller
Power Supply	AC 100~120V/AC220~240V Auto Changeable, 50/60Hz ±1Hz
Operating Environment	Temperature: 68~89.6°F (20~32°C) Humidity: 40~60% (no condensation)
Certifications	FCC(USA), VCCI(Japan)
Machine Dimensions (W x D x H)	73.8" x 28.1" x 47.9" (including Stand)
Take-up Roll System	Standard

**Vinyl Express Q54 Specifications**

- Configuration: Digital Servo Friction feed with MicroGrit rollers drive
- Windows OS compatible only
- Maximum Cutting Width Vinyl Express Q54: 54 in.
- Maximum Media Width Vinyl Express Q54: 60.2 in.
- Cutter Force: 10-400 grams down force
- Cutting Acceleration: 4g
- Max. Cutter Speed: 50ips
- Cutting Method: Friction-fed, high-speed drag blade with Soft Blade Landing and Tangential blade control mode
- Min. Character Size: 0.125" high, alpha-numeric characters, varies with type of film and font
- Min. Character Matrix: 0.125" high, Alpha-numeric characters, varies with type of film and font
- Mechanical Resolution: 0.0002"
- Repeatability: 0.0039" over 80" travel or better
- Number of Tool Holders: 1(accepts cutting blade, plotting pen, and pouncing tool)
- Blade Types: Super steel, ceramic
- Pen Types: Water-based fiber tip, roller ball, and ceramic tip
- Buffer: 2MB
- Ports: RS-232C Serial & USB
- Commands: HP-GL, GP-GL, control panel selectable
- Control Panel: 20 digits x 4 lines LCD with comprehensive icon corresponding soft keys
- Media Supply: Integrated Accuload media supply system, optional media racks (3 additional max.) for tandem holding of up to 4 vinyl rolls
- Media Pre-Feed: Standard (built-in Smart Feed function automatically unwinds and pre-feeds media for a specified distance upon self-recognition of plot file length)
- Power Supply: AC 100-240V, 48-62 Hz, auto switching, 120 VA max
- Operating Environment: 50 degrees to 95 degrees F
- Pouncing Function: With optional tool
- Includes Stand
- Warranty: 2 years, parts and labor