

## ROLAND SOLJET Pro 4 XR-640 Printer/Cutter



Rating: 5.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 11,997.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Roland](#)

Description

**Specifications :**

<b>Printing technology</b>	Dual Head Piezoelectric Inkjet		
<b>Media</b>	Width	10.2 to 64 in. (259 to 1625 mm)	
	Thickness	Maximum 39 mil (1.0 mm) with liner	
	Roll diameter	Maximum 8.3 in (210 mm)	
	Roll weight	Maximum 88 lbs (40 kg)	
	Core diameter	3 in (76.2 mm) or 2 in (50.8 mm)	
<b>Printing Width</b>		Max. 63 in. (1600 mm)	
<b>Ink cartridges</b>	Type	Roland Eco-Sol MAX 2 Ink	
	Capacity	440 cc CMYKLCmLk - 220 cc Metallic and White	
	Colors	9 Colors (cyan, magenta, yellow, black, light cyan, light magenta, light black, metallic, white)	
<b>Print resolution</b>	Dots per in	Maximum 1,440 dpi	
<b>Print Modes</b>			
<b>Quality</b>	Resolution	Pass Count	Speed
<b>Billboard (Banner)</b>	360x360	1	528.1 sqft/hr (49.1 m <sup>2</sup> /h)

<b>High Speed (Banner)</b>	540x360	2	351.9 sqft/hr (32.7 m <sup>2</sup> /h)
	540x360 (V)	3	232.4 sqft/hr (21.6 m <sup>2</sup> /h)
<b>Standard (Banner)</b>	360x720	3	183.5 sqft/hr (17.0 m <sup>2</sup> /hr)
	540x720	5	110.1 sqft/hr (10.2 m <sup>2</sup> /hr)
<b>High Quality (Banner)</b>	720x1440	10	50 sqft/hr (4.6 m <sup>2</sup> /h)
<b>High Speed (Vinyl)</b>	540x360	3	232.4 sqft/hr (21.6 m <sup>2</sup> /h)
<b>Standard (Vinyl)</b>	360x720	4	166.1 sqft/hr (15.4 m <sup>2</sup> /h)
	540x720	6	109.7 sqft/hr (10.2 m <sup>2</sup> /h)
<b>High Quality (Vinyl)</b>	720x1440	10	48.7 sqft/hr (4.5 m <sup>2</sup> /h)
<b>Distance accuracy</b>	Error of less than ±0.3% of distance traveled, or ±0.3 mm, whichever is greater		
<b>Media heating system</b>	Print heater		Setting range for the preset temperature: 86 to 112°F (30 to 45°C)
	Dryer		Setting range for the preset temperature: 86 to 122°F (30 to 50°C)
<b>Connectivity</b>	Ethernet (10BASE-T/100BASE-TX, automatic switching)		
<b>Power-saving function</b>	Automatic sleep feature		
<b>Power requirements</b>	AC 100 to 120 V ±10%, 8.2A, 50/60 Hz or AC 220 to 240 V ±10%, 4.2A, 50/60 Hz		
<b>Power consumption</b>	During operation		1530 w
	Sleep mode		47 w
<b>Environmental</b>	Power on		Temperature: 59 to 90°F (15 to 32°C) [68°F (20°C) or more recommended], Humidity: 35 to 80% RH (no condensing)
	Power off		Temperature: 41 to 104°F (5 to 40°C), humidity: 20 to 80% RH (no condensation)
<b>Dimensions (with stand)</b>	116[W] x 47.8[D] x 49.6[H] in (2948[W] x 1214[D] x 1260[H] mm)		
<b>Weight (with stand)</b>	452 lb (205 kg)		
<b>Included items</b>	XR-640 stand, cleaning liquid cartridges, power cord, media clamps, blade, blade holder, replacement blade for sheet cutter, Roland VersaWorks RIP Software, cleaning kit, manual, etc.		

## Roland VersaWorks System Requirements

<b>Operating System</b>	Windows® 7 (32-bit, 64-bit)
	Windows Vista® (32-bit, 64-bit)
<b>CPU</b>	Windows® XP (32-bit, 64-bit)
<b>RAM</b>	Core™2 Duo, 2.0 GHz or faster recommended
<b>Video card and monitor</b>	2 GB or more recommended
<b>Free hard-disk space</b>	A resolution of 1280 x 1024 resolution or more recommended
<b>Hard-disk file system</b>	40 GB or more recommended
<b>Optical drive</b>	NTFS format
	DVD-ROM drive

## Application software compatible with Cutting and Print&Cut

Adobe® Illustrator® 10, CS, CS2, CS3, CS4, CS5, CS6  
CorelDRAW® 11, 12, X3, X4, X5