

Spectra Polaris PQ-512/35 AAA Printhead



Rating: 5.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 616.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Spectra](#)

Description

Spectra Polaris PQ-512 / 35 AAA Printhead

To be used with: ORASIGN W-320PQ, ORASIGN W-180PQ, WIT-COLOR ULTRA4000 4H/6H, WIT-COLOR ULTRA4000 8H, Flora LJ320P, GONGZHENG GZT3204, GONGZHENG GZT3202, GONGZHENG GZR3208, GONGZHENG GZT3208AU, JHF A8 3304PQ, JHF A8 3308PQ, LEOPARD Q8 3304PQ, LEOPARD Q8 3308PQ, APRINT 330P, DGI PQ-3202 / PQ-3204, Eurotech Turbo, Flora HJII 5000UV, Wit-Color Ultra 4000-3304 / Ultra 4000-3308, JHF Vista Q8 3304PQ / Q8 3308PQ, Gongzheng StormJet T3208AU, Kornit Paradigm 933

Remarks: original


Description:

- The Polaris PQ-512 / 35 AAA Printhead has 512 independent channels arranged in multiple rows at 200 dots-per-inch spacing for single color operation, or 100 dots-per-inch spacing for two color operation.

- The printhead is designed for binary jetting using a 35-picoliter native drop size with 8-meters per second nominal drop velocity for jetting fluids in the 8 to 20 centipoise range. Using VersaDrop jetting technology, the printhead is capable of adjustable binary operation at drop sizes up to 80 picoliters with resolution up to 800 dpi.
- Building upon the legendary reliability and performance of the Spectra Nova and Galaxy Printheads, the Polaris PQ-512 AAA family of printheads uses field proven materials and a repairable design to deliver a long service life and consistent output. And by leveraging the inherent flexibility of the Q-Class platform, the Polaris PQ-512 AAA offers even greater jetting performance, nozzle packing density, and configuration flexibility.
- The PQ-512 / 35 AAA Printhead is compatible with a broad range of inks, including UV-curable, aggressive organic solvent and aqueous inks and associated maintenance fluids.
- The unique design of Polaris PQ-512 / 35 AAA Printhead allows each 256-channel module to be replaced and accurately registered in the field with no special tools or recalibration. An integral mounting bezel with precision registration points enables drop-in alignment with other carriage features.
- Two electrical connectors contain eight serial data lines that supports fire frequencies in excess of 50 kHz.
- The flexible fluid interface allows single and two-color operation. Each 256-channel module is dual ported to facilitate easy priming, flushing and ink recirculation. Heaters and temperature sensors allow precise control of ink viscosity at jetting temperatures up to 60°C.

Features:

- 35 picoliter nominal drop size;
- 512 individual addressable nozzles;
- Incorporates VersaDrop™ binary jetting capability;
- Excellent channel-to-channel uniformity;
- High frequency continuous operation;
- Designed for long service life;
- Supports UV-curable, solvent, and aqueous-based inks;
- Configurable for single- and two-color operation;
- Integral mounting bezel with precision features;
- Optimized for high viscosity jetting fluids;
- Built-in heaters and temperature sensors;
- Operation up to 60°C [140°F];
- Simplified field repair with no special tools required.



Model	PRH-SPE-006
Number of addressable jets	512
Print width	64.897 mm (2.555 inches)
Single color (4 rows of jets)	127 microns [0.005 in.] (200 dpi)
Two color (2 rows of jets/per color)	254 microns [0.010 in.] (100 dpi)
Jet straightness, 1 sigma*	2.0 mrad [0.11°]
Nominal drop velocity	8 m/s
Calibrated drop mass	35ng
Compatible jetting fluids	UV-curable, organic solvents, aqueous
Adjustment for drop size	35 - 80 picoliters
Drop Size 35 pl	Maximum Frequency 30 kHz
Drop Size 80 pl	Maximum Frequency 13 kHz
Operating temperature	up to 60° C

range	
Fluid viscosity at jetting	8 to 20 centipoise
Dry weight	160 grams

Application:

The Spectra Polaris PQ-512/35 AAA Printhead is a high performance inkjet printhead designed for a broad range of industrial and commercial printing applications at resolutions up to 800 dpi. Robust construction and repairable design make it ideal for solvent, UV and aqueous based wide format printers built for demanding production environments