

Canon XF105 HD Professional Camcorder



Rating: 5.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,249.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Canon](#)

Description

Product Highlights

Camcorder : Canon XF105 HD Professional Camcorder

- 1/3" CMOS Sensor
- 1920x1080 at 24p/30p/60i
- 50 Mbps MPEG-2 4:2:2 Recording
- MXF File Format
- Dual CF Card Slots
- 10x Zoom Lens
- Multiple Bit Rates & Resolutions
- Dual XLR Inputs
- HD/SD-SDI, SMPTE Timecode, Genlock

Image Device

Lens

Front Filter Thread Size

Horizontal Resolution

Focusing System

Minimum Illumination

Built-in Filters

Minimum Focus Distance

Video Recording System

1/3" CMOS Sensor

2.37MP (2.07MP effective)

10x HD Zoom

4.25 to 42.5 mm (30.4 to 304 mm, 35mm equivalent)

f/1.8 to 2.8

58 mm

900 TV lines or more

TVAF plus External Phase Difference Metering Sensor

Autofocus (Instant AF, Medium AF, Normal AF, Face AF, Face Only AF), Manual, Full Manual

4.5 lux (full AUTO mode, 1/60 shutter speed, +24 dB gain)

1.6 lux (manual mode, 1/4 shutter speed, +33 dB gain)

Neutral density (Auto or Off)

20 mm (wide macro)

60 cm (entire zoom range)

Compression: MPEG-2 Long GOP

Color Space: 4:2:2 (at 50 Mbps recording)

File Format: MXF

Recording Modes:

50 Mbps (CBR) 4:2:2, 1920x1080, (60i/30p/24p),

1280x720 (60p/30p/24p)

35 Mbps (VBR) 4:2:0, 1920x1080 (60i/30p/24p),

1280x720 (60p/30p/24p)

25 Mbps (CBR) 4:2:0, 1440x1080 (60i/30p/24p)

2-Channel, PCM digital recording, 16-Bit; 48 kHz

60i, 60p (720p mode only), 30p, 24p

SuperRange Optical (Lens Shift) 4 Modes: Standard, Powered, Dynamic, Off

3.5" color, approx. 920,000 dots

0.24" color, approx. 260,000 dots

Stereo electret condenser microphone

CF Card: 2 Slots (movie files only)

SD Card: Still images, Custom Picture Data, Clip Metadata, Custom Settings

Max 1/2000

Auto, Manual, Custom (2000K to 15000K in 100K increments), Daylight, Tungsten

Not specified by manufacturer

64 GB Compact Flash (CF) card

(Greater capacity is possible when two cards are used)

25 Mbps: 310 minutes

35 Mbps: 225 minutes

50 Mbps: 160 minutes

1 x HD/SD-SDI output (BNC)

1 x HDMI output (Type A)

1 x Component video output

1 x 3.5 mm A/V terminal for composite video output

2 x 3-pin XLR input (Mic/Line)

1 x Timecode/Genlock terminal 1 x Mini-USB 2.0

1 x 3.5 mm stereo mini-jack

1 x LANC remote control terminal

7.4 VDC (Battery Pack)

Not specified by manufacturer

32 to 104°F (0 to 40°C), 85% relative humidity

Audio Recording Format

Frame Rates

Image Stabilization

LCD Monitor

Viewfinder

Microphone

Memory Card Slot

Shutter Speed

White Balance

Gain Selection

Maximum Recording Time

Input and Output Connectors

Power Requirements

Power Consumption

Operating Temperature

Dimensions (WxHxD)	4.8 x 5.8 x 9.8" (12.1 x 14.8 x 25 cm)
Weight	2.4 lbs (1.08 kg) (not including battery, memory card, lens hood, mic holder)
Packaging Info	
Package Weight	6.7 lb
Box Dimensions (LxWxH)	12.6 x 9.1 x 8.0"