

HP DesignJet T1530 36in Postscript Printer



Rating: 4.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 3,497.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

Item: L2Y24A
UPC: 889296269687

Printing Method	HP Thermal Inkjet
Printing Technology	Up to 2400 x 1200 optimized dpi
Maximum Resolution	Print Time Line Drawing: 21 sec/page on A1/D (economode)
Print Speed	Print Speed Line Drawing: 120 A1/D prints per hour (economode)
Ink Type	Dye Based: C, G, M, Pk, y Pigment Based: mK

Printers : HP DesignJet T1530 36in Postscript Printer

Ink Droplet Size	6 pL (C, M, Y, G, pK) 9 pL (mK)
Ink Cartridge Configuration	6 Cartridges: cyan, gray, magenta, matte black, photo black, yellow
Ink Cartridge Capacity	130 or 300 mL
Margins	Top x Bottom x Left x Right: Roll: 0.12 x 0.12 x 0.12 x 0.12" (3 x 3 x 3 x 3 mm) Sheet: 0.12 x 0.87 x 0.12 x 0.12" (3 x 22 x 3 x 3 mm) ±0.1%
Line Accuracy	C, G, M, mK, pK, Y
Printhead	0.79 mil (0.02 mm) (HP-GL/2 addressable)
Minimum Line Width	2.8 mil (0.07 mm) (ISO/IEC 13660:2001(E))
Guaranteed Minimum Line Width	Black: 2.15 D (6 L* min)
Maximum Optical Density	Line drawings, Renderings, Presentations
Applications	96 GB (file processing)
Memory	500 GB
Hard Disk	
Media Types & Handling	
Paper Handling	Input: two automatic front-loading roll feeds, smart roll switching, sheet feed Output: integrated output stacking tray (from A4/A to AO/E, with up to 50 A1/D-size capacity), media bin, automatic cutter
Paper Types	Bond and coated paper (bond, coated, heavyweight coated, super heavyweight plus matte, colored), technical paper (natural tracing, translucent bond, vellum), film (clear, matte, polyester), photographic paper (satin, gloss, semi-gloss, matte, high-gloss), backlit, self-adhesive (two-view cling, indoor paper, polypropylene, vinyl)
Media Sizes	Standard: Rolls: 11 to 36" (27.9 to 91.4 cm) Sheets: 8.3 x 11 to 36 x 48" (21 x 27.9 to 91.4 x 121.9 cm) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Custom: 8.3 x 11 to 36 x 48" (21 x 27.9 to 91.4 x 121.9 cm) External Diameter: 5.5" (14 cm) Up to 19.7 mil (0.5 mm)
Roll	
Media Thickness	
Connectivity	
Interfaces	Standard: Gigabit Ethernet (1000Base-T) Hi-Speed USB 2.0
Printer Language	Postscript Printer: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP-PCL3GUI, URF Basic Printer: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP-PCL3GUI, URF
Printing Paths	Direct printing from USB flash drive, email printing, HP driver for Windows, HP driver for Mac OS X, HP Print Service for Android, Apple AirPrint driver
Drivers	Included: HP-GL/2, HP-PCL3GUI drivers for Windows and Mac OS X; PostScript drivers for Windows, Linux, and Mac OS X
Physical	
Temperature	Operating: 41 to 104°F (5 to 40°C) Storage: -13 to 131°F (-25 to 55°C)
Operating Humidity	20 to 80% RH
Acoustic Noise	Sound Pressure: 47 dB(A) (printing); 39 dB(A) (ready); Sound Power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)
Power Consumption	Printing: 120 W Sleep: 1.3 W (5 W with embedded Digital Front End) Auto Ranging: 100 to 240 VAC (±10%), 50/60 Hz (±3 Hz)
Input Voltage	2 A maximum
Input Current	Safety
Certifications	USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EPEAT Bronze

Printers : HP DesignJet T1530 36in Postscript Printer

Dimensions (WxDxH)	55.1 x 36.1 x 43.7" (139.9 x 91.6 x 111 cm)
Weight	194 lb (88 kg)