HP DesignJet T790 24in ePrinter



Rating: 3.0
Price:
Variant price modifier:

Price with discount:

Salesprice with discount:

USD 1,800.00

Discount:

In Stock!
Ready to Order

Ask a question about this product

Manufacturer: Hp

Description
Item: CR648AB1K

UPC: 886111274611

Printing Method	Thermal inkjet
Printing Technology	1200 dpi (optimized: 2400 x 1200 dpi)
Maximum Resolution	**Cyan, Gray, Magenta, Photo Black:** 6 pl **Matte Black, Yellow:** 9 pl
Minimum Ink Droplet Size	**Cyan, Gray, Magenta, Photo Black, Yellow:** dye-based
Ink Type	

	Matte Black: pigment-based
Ink Palette	Cyan, gray, magenta, matte black, photo black, yellow
Ink Cartridge Configuration	6 individual ink cartridges, 3 Printheads (gray & photo black, matte black & yellow, magenta & cyan)
Line Accuracy	±0.1%
Performance	
Print Speed	**Normal:** 93 D prints per hour **Line Drawing:** 72 D prints per hour **Best Drawing:** 30 ft²/hr **Image Draft** 400 ft²/hr
Paper Handling	
Maximum Paper Width	24.0" (610 mm)
Maximum Printable Area	24.0" x 300.0' (610 mm x 91.44 m)
Margins	**Sheet:** 0.2 x 0.67 x 0.2 x 0.2" (5 x 17 x 5 x 5 mm) **Roll:** 0.2 x 0.2 x 0.2 x 0.2" (5 x 5 x 5 x 5 mm)
Paper Sizes	**Sheet:** 8.26 x 11.0 to 24.0 x 66.0" (210 x 279 to 610 x 1676 mm) **Roll:** 11.0 to 24.0" (279 to 610 mm) rolls
Paper Types	**Bond And Coated Paper:** bond, coated, heavyweight coated, super heavyweight plus matte **Technical Paper:** natural tracing, translucent bond, vellum **Film:** clear, matte **Photographic Paper:** satin, gloss, semi-gloss, matte, high-gloss **Self-Adhesive:** polypropylene, vinyl
Special Media Support	Technical paper, film, self-adhesive paper
Media Weight	60 to 328 g/m²
Media Thickness	Up to 0.8 mm (31.5 mil)
Maximum Media Roll Diameter	5.3" (134.62 mm) external diameter
Maximum Roll Print Length	300.0' (91 m)
Paper-Feed Method	Sheet feed, roll feed, automatic cutter
Connectivity	
Computer Interface	Fast Ethernet (100Base-T), Hi-Speed USB 2.0 certified, EIO Jetdirect accessory slot
Printer Language	Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI
Drivers	HP-GL/2, HP-RTL drivers for Windows (optimized for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers
Network Capable	Fast Ethernet (100Base-T)
OS Compatibility	**Microsoft:** Windows 7 Ultimate/Professional/Home Premium, Windows Vista Ultimate/Business/Home Premium, Windows XP (32-bit, 64-bit) Professional/Home, Windows Server 2008 (32-bit, 64-bit), Windows Server 2003 (32-bit, 64-bit) **Mac:** OS X v 10.5, v 10.6 **Citrix:** XenApp, XenServer **Linux**
Windows System Requirements	**Windows XP:** (SP2 or later) Intel Pentium family or AMD K6/Athlon/Duron family (1 GHz) 1 GB RAM 2 GB available hard disk space **Windows Vista:** 32-bit (x86) or 64-bit (x64) processor (1 GHz) 2 GB RAM 2 GB available hard disk space
Apple System Requirements	OS X v 10.4, OS X v 10.5 PowerPC G4, G5, or Intel Core Processor 1 GB RAM 2 GB available hard disk space
Environmental	
Temperature	**Operating Temperature:** 41 to 104 ºF (5 to 40 °C) **Storage Temperature:** -13 to 131 ºF (-25 to 55 ºC)
Humidity	**Operating Humidity:** 20 to 80% RH **Storage Humidity:** 0 to 95% RH
Acoustic Noise	**Sound Pressure:** active - 46 dB(A); standby - 29 dB(A) **Sound Power:** active - 6.3 B(A); standby - 4.4 B(A)
Physical	
Buffer/Ram	8.0 GB
Hard Drive Space	160 GB
Power Consumption	**Printing:** < 120 Watts **Powersave:** < 7 Watts **Off:** 0.1 Watts

Power Requirements	100 to 240 VAC (±10%), 50/60 Hz (±3 Hz), 2 A max
Dimensions	49.7 x 27.6 x 41.3" (1262 x 702 x 1050 mm)
Weight	132.0 lb (60.0 kg)
Packaging Info	
Package Weight	190.0 lb
Box Dimensions (LxWxH)	56.2 x 30.1 x 24.0"