

## HP DesignJet T930 36in Printer



Rating: 4.0

**Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,247.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

**Item:** L2Y21A

**UPC:** 889296269557

Printing Method	HP Thermal Inkjet
Printing Technology	Up to 2400 x 1200 optimized dpi
Maximum Resolution	Print Time Line Drawing: 21 sec/page on A1/D (economode)
Print Speed	Print Speed Line Drawing: 120 A1/D prints per hour (economode)

## Printers : HP DesignJet T930 36in Printer

---

Ink Droplet Size	6 pL (C, M, Y, G, pK); 9 pL (mK)
Ink Type	5 dye-based (C, M, Y, G, pK; pigment-based (mK)
Ink Cartridge Configuration	6 individual ink cartridges (cyan, gray, magenta, matte black, photo black, yellow)
Ink Cartridge Capacity	130 or 300 mL
Margins	Top x Bottom x Left x Right: Roll: 0.12 x 0.12 x 0.12 x 0.12" (3 x 3 x 3 x 3 mm) Sheet: 0.12 x 0.87 x 0.12 x 0.12" (3 x 22 x 3 x 3 mm)
Line Accuracy	±0.1%
Printhead	1 (C, G, M, mK, pK, Y)
Minimum Line Width	0.8 mil (0.02 mm) (HP-GL/2 addressable)
Guaranteed Minimum Line Width	2.8 mil (0.07 mm) (ISO/IEC 13660:2001(E))
Maximum Optical Density	Black: 2.15 D (6 L* min)
Applications	Line drawings, renderings, presentations, maps, orthophotos
Memory	64 GB (file processing) 320 GB
Media Types & Handling	
Paper Handling	Input: Automatic front-loading roll feeds, sheet feed Output: Integrated output stacking tray (from A4/A to AO/E, with up to 50 A1/D-size capacity), media bin, automatic cutter
Paper Types	Bond and coated paper (bond, coated, heavyweight coated, super heavyweight plus matte, colored), technical paper (natural tracing, translucent bond, vellum), film (clear, matte, polyester), photographic paper (satin, gloss, semi-gloss, matte, high-gloss), backlit, self-adhesive (two-view cling, indoor paper, polypropylene, vinyl)
Media Sizes	Standard: Rolls: 11 to 36" (27.9 to 91.4 cm) Sheets: 8.3 x 11" to 36 x 48" (21 x 27.9 to 91.4 x 121.9 cm) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E)  Custom: 8.3 x 11" to 36 x 48" (21 x 27.9 to 91.4 x 121.9 cm) External Diameter: 5.5" (14 cm) Up to 19.7 mil (0.5 mm)
Roll	
Media Thickness	
Connectivity	
Interfaces	Gigabit Ethernet (1000 Base-T)
Printer Language	HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF
Printing Paths	Direct printing from USB flash drive, email printing, HP driver for Windows, HP driver for Mac OS X, HP Print Service for Android, Apple AirPrint driver
Drivers	Included: HP-GL/2, HP-PCL3GUI drivers for Windows and Mac OS X
Physical	
Temperature	Operating: 41 to 104°F (5 to 40°C) Storage: -13 to 131°F (-25 to 55°C)
Operating Humidity	20 to 80% RH
Acoustic Noise	Sound Pressure: 47 dB(A) (printing); 39 dB(A) (ready); < 16 dB(A) (sleep) Sound Power: 6.5 B(A) (printing); 5.8 B(A) (ready); < 1.9 B(A) (sleep)
Power Consumption	120 W (printing), 1.3 W (sleep), and 5 W with embedded Digital Front End
Input Voltage	Auto Ranging: 100 to 240 VAC (±10%), 50/60 Hz (±3 Hz)
Input Current	2 A (maximum)
Certifications	Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS)  Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)  Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP, EPEAT Bronze
Dimensions (WxDxH)	55.1 x 36.1 x 43.7" (140 x 91.7 x 111 cm)
Weight	191.8 lb (87 kg)

