

HP DesignJet Z3200 PostScript 24in Photo Printer



Rating: 4.0
Price:
Variant price modifier:

Price with discount:
Salesprice with discount:

USD 1,950.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Hp](#)

Description

Item: Q6720BB1K
UPC: 884420403395

Printing Method	HP Thermal Inkjet
Printing Technology	1200 dpi
Maximum Resolution	Adobe PostScript 3, Adobe PDF 1.6, TIFF, JPEG, HP PCL 3 GUI
Printer Language	4.0 pl: Light cyan, light magenta, light gray, photo black, gray, gloss enhancer
Ink Droplet Size	6.0 pl: Magenta, yellow, matte black, chromatic red, green, blue
Ink Type	HP Vivera pigment inks
Ink Palette	Blue, green, magenta, chromatic red, yellow, gray, photo black, matte

Printers : HP DesignJet Z3200 PostScript 24in Photo Printer

Ink Cartridge Configuration	black, light cyan, light gray, light magenta 6 printheads: 1: light magenta & light cyan printhead 2: magenta & yellow printhead 3: photo black & light gray printhead 4: blue & green printhead 5: matte black & chromatic red printhead 6: gloss enhancer & gray printhead
Number of Nozzles	2112 per printhead (1056 nozzles per color)
Print Speed	Best (Glossy): 12.4 min/page on D/A1 Normal (Glossy): 7.2 min/page on D/A1 Normal (Coated): 3.8 min/page on D/A1 Draft (Coated): 2.0 min/page on D/A1
Input Buffer	256 MB
Storage Capacity	80 GB hard disk
Print Archival Life	Approximately 200 years fade resistant
Waterproofing	Water-resistant on a range of HP creative and specialty media
Paper Handling	
Maximum Paper Width	24.0" (60.96 cm)
Maximum Printable Area	Sheets: 24.0 x 66.0" (60.96 x 167.64 cm) Rolls: 24.0" x 300.0' (60.96 cm x 91.44 m)
Paper Types	Photo: Satin, Gloss, Semi-Gloss, Matte, Baryte Paper Proofing: Semi-Gloss, High-Gloss Contract, Semi-Gloss Contract, Matte Fine Art: Smooth, Textured, Watercolor, Satin, Aquarella, Litho-Realistic, Canvas Self-Adhesive: Indoor, Vinyl, Polypropylene Banner/Sign: Display Film, Indoor Banner, Scrim, Polypropylene, Tyvek, Outdoor, Billboard, PVC-Free Bond & Coated: Bond, Coated, Heavyweight Coated, Super Heavyweight Plus Matte, Colored Technical: Tracing, Translucent Bond, Vellum Film: Clear, Matte, Polyester Backlit Fabric/Textile: Flag, Polyester, Silk Satin, vellum, canvas, Tyvek, banners, backlit Up to 31.5 mil (0.8 mm) Up to 133 lb (500 g/m²) 300' (91.44 m) 5.3" (13.46 cm) Sheet feed, roll feed, automatic cutter (cuts all media except canvas)
Special Media Support	
Media Thickness	
Media Weight	
Maximum Roll Print Length	
Maximum Media Roll Diameter	
Paper-Feed Method	
Connectivity	
Computer Interface	Hi-Speed USB 2.0 certified port, 1000Base-T Ethernet RJ-45 port (1000Base-T for PS models), EIO Jetdirect accessory slot
Network Capable	1000Base-T Ethernet RJ-45 port
PostScript Support	Adobe PostScript 3
OS Compatibility	Microsoft: Vista, Vista x64, XP Home, XP Pro, XP Pro x64, Server 2008 (32/64-bit), Server 2003 (32/64 bit), Terminal Services Mac: OS X v 10.4, 10.5, 10.6 Citrix: MetaFrame
Physical	
Status Display	Error, warnings; ink, paper, & printer status
Front Panel Controls	Check ink/paper status, unload paper, form feed and cut, menu, ok, 4 navigation keys, cancel, power
Power Consumption	200 W (maximum)
Power Requirements	100 to 240 V AC (±10%), 50/60 Hz (±3 Hz), 2 Amps max
Temperature & Humidity	Operating Temperature: 41 to 104 °F (5 to 40 °C) <i>Recommended: 59 to 95 °F (15 to 35 °C)</i> Storage Temperature: -13 to 131 °F (-25 to 55 °C) Operating Humidity: 20 to 80% Storage Humidity: 0 to 95%
Acoustics	Sound Power Level - Idle: 4.4 B(A) Sound Power Level - Operating: 6.5 B(A) Sound Pressure - Idle: 29 dB(A) Sound Pressure - Operating: 49 dB(A) 49.7 x 27.2 x 41.2" (126.2 x 69.0 x 104.7 cm) 143 lb (65 kg)
Dimensions	
Weight	
Packaging Info	
Package Weight	201.0 lb

Box Dimensions (LxWxH)

56.5 x 30.5 x 28.0"