HP DesignJet Z5200 Postscript 44in Printer







Rating: 5.0 **Price:**

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,247.00

Discount:



Ask a question about this product

Manufacturer: Hp

Description

Item: CQ113A

UPC: 884962858080

Printing Method

Printing Technology Maximum Resolution Minimum Ink Droplet Size

Ink Type Ink Palette

Ink Cartridge Configuration Performance

Print Speed

Input Buffer

Paper Handling Maximum Paper Width Maximum Printable Area

Paper Sizes

Borderless Photo Sizes

Paper Types

Special Media Support Media Thickness Maximum Media Roll Diameter Maximum Roll Print Length Paper-Feed Method Connectivity Computer Interface

Network Capable Graphics Support

Windows System Requirements Mac OS System Requirements Physical Status Display Buffer/Ram Image Preview Display

Power Consumption

Front Panel Controls

Power Requirements

Dimensions
Weight
User-Replaceable Items
Operating Temperature
Storage Temperature
Operating Humidity
Acoustic Noise

Certification Safety Compliance

Electromagnetic Compatibility

Environmental Compliance Packaging Info

HP Thermal Inkjet

Up to 2400 x 1200 optimized dpi

Light cyan, light magenta, light grey, photo black: 4 pl

Cyan, magenta, yellow, matte black: 6 pl

HP Vivera pigment ink

Cyan, magenta, yellow, light cyan, light gray, light magenta, matte

black, photo black 8 individual ink cartridges

Line drawings: 42 sec/page on D, 42.1 D prints/hour

Color: Fast - 445 ft2/hr on plain media, Best - 5.1 min/page on D or up to

58 ft²/hr on glossy media

32 GB (virtual memory capacity)

160 GB hard disk

44.0"

Sheets: 44.0 × 66.0" Rolls: 11.0 - 44.0"

Sheets: 8.5 × 11" - 44 × 66"

Rolls: 11 to 44"

Standard: narrow margin

Oversize: image printed on a page slightly larger than the size selected

and cut by printer

Borderless: image is slightly enlarged to ensure that no margin is left

between the edges of the image and the edges of the paper

Photographic, proofing, fine art printing material, self-adhesive, banner

and sign, bond and coated, backlit, fabric/textile

Backlit, fabric, textile

?31.5 mil 44.0"

300.0' (91.44 m)

Sheet feed, roll feed

Gigabit Ethernet (1000Base-T); Hi-Speed USB 2.0 certified; EIO

Jetdirect accessory slot

Ethernet

Languages supported: HP-PCL3 GUI, CALS/G4, PostScript, PDF,

TIFF, JPEG XP or newer 10.4 or newer

Error, warning, and usage information

32 GB RAM; 160 GB hard disk

N/A

Ink levels, paper type, unload paper, form feed and cut, menu, ok, 4

directional keys, cancel, power

Maximum: 170 watts

Power Save: < 12 watts (< 30 watts with embedded DFE)

Off: 0.1 watts

Input voltage (auto ranging) 100 to 240 VAC (±10%), 50/60 Hz (±3 Hz),

2 A max

 $69.7 \times 27.2 \times 41.2$ " (177.03 × 69.08×104.65 cm)

189 lb (85.73 kg)

Print heads (4), ink cartridges (8)

41 - 104° F (5 - 40° C) -13 - 131 °F (-25 - 55 °C)

20 to 80% relative humidity

Sound pressure: active - 49 dB(A), standby - 29 dB (A)

Sound power: active - 6.5 B(A), standby - 4.4 B(A)

USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE)

Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)

WEEE; EU ROHS; China ROHS; REACH; EuP; FEMP

Package Weight Box Dimensions (LxWxH) 249.0 lb 75.5 x 30.5 x 30.0"