## HP DesignJet Z5400 44in Postscript Printer











Rating: 3.0 **Price:** 

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 2,997.00

Discount:



Ask a question about this product

Manufacturer: Hp

Description Item: E1L21AB1K

**UPC**: 887758705452

Printing Method Print Resolution

Up to 2400 x 1200 optimized dpi

Margins

Ink Types Line Accuracy

Minimum Line Width

Guaranteed Minimum Line Width

Image Quality

Short Term Color Stability

Long Term Print-to-Print Repeatability

Maximum Optimal Density

Media Handling

Size

Thickness Memory

Memory Amount

Connectivity Interface

**Print Languages** 

Printing Paths

Driver Acoustics Sound Pressure

Sound Power

Power Consumption

Requirements

Environmental
Operating Temperature
Storage Temperature
Operating Humidity (Relative)

Certifications Safety

Electromagnetic Compliance

Environmental General Dimensions

Weight

Packaging Info

Roll: 0.2 x 0.2 x 0.2 x 2" / 5 x 5 x 5 x 5 mm (borderless on photo roll

media)

Sheet: 0.2 x 0.7 x 0.2 x 0.2" / 5 x 17 x 5 x 5 mm

Pigment-based

+/- 0.1% (of the specified vector lens or +/- 0.008" / 0.2 mm [whichever greater] at 73°F / 23°C, 50-60% relative humidity, on A0/E HP Matte

Film in Best or Normal mode with Original HP inks)

0.0015" / 0.04 mm (HP-GL/2 addressable)

0.0031" / 0.08 mm (ISO/IEC 13660:2001 (E); measured on HP Matte

Film)

< 1 dE2000 in less than 5 minutes (with HP Premium Instant Dry Photo

Satin media with Original HP inks, right after calibration)

Average < 0.5 dE2000, 95% of colors < 1.4 dE2000 (with HP Premium Instant Dry Photo Satin media with Original HP inks, right after calibration)

4 L\* min/2.5 D (with HP Premium Instant Dry Photo Gloss media with Original HP inks)

Two automatic roll feeds Smart roll-switching Sheet feed

Media output bin

Automatic cutter (cuts all media except canvas and banners) Sheets:  $8.3 \times 11$ " to  $44 \times 66$ " /  $21 \times 27.9$  cm to  $111.8 \times 167.6$  cm

Rolls: 11 to 44"-wide / 27.9 to 111.8 cm-wide

Up to 19.7 mil / 0.5 mm

64 GB (virtual; based on 640 MB RAM)

320 GB hard disk

Gigabit Ethernet (1000BASE-T), Hi-Speed USB 2.0, EIO Jetdirect

accessory slot

Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP PCL 3

GUI, HP-GL/2, HP-RTL

Printer driver, HP Embedded Web Server, HP Instant Printing PRO,

USB, email printing

PostScript Windows and Mac drivers

Active: 45 dB(A) Standby: 23 dB(A) Active: 6.7 B(A) Standby: 4.1 B(A)

Printing: < 120 W Ready: < 27 W

Sleep: < 5 W (< 22 W with embedded digital front end)

Off: 0.1 W

100-240 VAC (+/- 10%; auto-ranging)

50/60 Hz (+/- 3 Hz) 2 A max

41-104°F / 5-40°C -13-131°F / -25-55°C 20-80% (non-condensing)

USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia/Kazakhstan (EAC), Singapore (PSB), China (CCC), Argentina

(IRAM), Mexico (NYCE)

Compliant with Class B requirements: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM),

China (CCC), Japan (VCCI)

Certified as Class A product: Korea (KCC)

ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH

Printer: 69.7 x 28.4 x 41.3" / 177.0 x 72.1 x 105.0 cm Shipping: 76 x 30.3 x 28" / 193.0 x 77.0 x 71.0 cm

Printer: 189.6 lb / 86 kg Shipping: 253.5 lb / 115 kg Package Weight Box Dimensions (LxWxH) 253.0 lb 69.7 x 41.3 x 28.4"