

Mutoh ValueJET 426UF 19" UV-LED Desktop Color Printer



Rating: 4.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 9,997.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Mutoh](#)

Description

Spec :

| | | | | |
|--|--|-----------|----------------|---------------|
| Print Technology | Drop-on-demand Micro Piezo Inkjet Technology | | | |
| Print Head | 1 | | | |
| Nozzle Configuration | 180 nozzles x 8 lines | | | |
| Drop Mass Range (pl) | 3.8 to 28 | | | |
| LED UV lamp life | 14.250 hours | | | |
| ValueJet 426UF - Media Specifications | | | | |
| Size Print Table | 483 mm (19") x 329 mm (12,95") | | | |
| Max. Print Area | 473 mm (18,62") x 319 mm (12,55") | | | |
| Max. Media Thickness | Up to 70 mm (2,75") | | | |
| Max. Media Weight | 4 kg | | | |
| Media Drying System | Long life LED UV curing lamp | | | |
| Vacuum System | Standard integrated - electronically adjustable hold-down strength | | | |
| ValueJet 426UF - Performance | | | | |
| | 4-colour setup | | 6-colour setup | |
| | CMYK | CMYK only | White only | Layer Print * |
| Speed in tables per hour (excl. unloading / loading time) ** | | | | |
| 1440 x 1440 Uni | 6 | 2 | 6 | 1 |
| 720 x 1440 Uni | 13 | 6 | 13 | 3 |

Printers : Mutoh ValueJET 426UF 19" UV-LED Desktop Color Printer

| | | | | |
|---|---|----|----|---|
| 720 x 1080 Bi | 28 | 14 | 28 | 7 |
| * : CMYK + White + Varnish | | | | |
| ** : 1 Table corresponds to 0,15 m ² | | | | |
| ValueJet 426UF - Ink Specifications | | | | |
| Ink Type | LED UV inks | | | |
| Ink Colours / Volume | CMYK & Varnish - 220 ml cassette White - 220 ml cassette | | | |
| Ink Setup | CMYK (CCMMYK) CMYK + White + Varnish (CMYK+Wh+Va) | | | |
| Ink Consumption * | 1.6 ml / table | | | |
| * : Average ink consumption at @720 dpi - coverage of 67 % | | | | |
| Compatibility | ABS, Alu Board, Glass, PC, PE, PET, PMMA (acrylic), PP, PS, PVC, Tyvek® * | | | |
| * : Ink adhesion will vary among media type and brand. Individual testing is required in function of your specific application. | | | | |
| ValueJet 426UF - Power Consumption | | | | |
| During Printing | < 330 Watt | | | |
| Power Supply | AC 100-120 V / AC 200-240 - 60/50 Hz - ? 4.0 A / ? 2.0 A | | | |
| ValueJet 426UF - Recommended Working Environment | | | | |
| Temperature | 20 °C - 32 °C with ?t: max. 2 °C/h | | | |
| Humidity | 40 % - 60 % (no condensation) with ?RH: max. 5 % RH/h | | | |
| ValueJet 426UF - Machine Measurements | | | | |
| Width x Depth x Height | 1188 x 839 x 545 mm | | | |
| Weight | 72 kg | | | |